

# Air Cylinder

ø32, ø40, ø50, ø63, ø80, ø100, ø125

New

RoHS


Weight **10%** lighter  
(ø40-100 stroke)

New Series **MB**

Current model

**0.91 kg** <<< **1.01 kg**

Reduced weight by  
changing the shape of  
the rod cover and  
head cover.



- Non-rotating rod type  
MBK-Z series (Single rod) and  
MBKW-Z series (Double rod) added.

**Series MB**



CAT.ES20-231D

## Part numbers with rod end bracket and/or pivot bracket available

Not necessary to order a bracket for the applicable cylinder separately

Note) Mounting bracket is shipped together with the product, but not assembled.

Example) **MDB****D**-40-100Z-**N****V**-M9BW

• Mounting style

### Pivot bracket

<b>Nil</b>	No bracket
<b>N</b>	Pivot bracket is shipped together with the product, but not assembled.

### Double clevis



### Center trunnion




### Rod end bracket

<b>Nil</b>	No bracket
<b>V</b>	Single knuckle joint
<b>W</b>	Double knuckle joint

### With rod end bracket

**V**: Single knuckle joint **W**: Double knuckle joint



\* Applicable to only D (Double clevis) and T (Center trunnion) mounting styles.

## Various mounting bracket options

- Suitable mounting brackets can be selected for the installation condition.
- Improved amount of mounting freedom

**N**: Double clevis pivot bracket

**D**: Double clevis

**C**: Single clevis

**G**: Head flange

**B**: Basic

**L**: Axial foot

**V**: Single knuckle joint

**W**: Double knuckle joint

**F**: Rod flange

**L**: Axial foot

**N**: Trunnion pivot bracket

**T**: Center trunnion

**N**: Trunnion pivot bracket

## Lightweight

Reduced weight by changing the shape of the rod cover and head cover.

Bore size [mm]	MB	Reduction rate [%]	Current model [kg]
32	0.66	8	0.72
40	0.91	10	1.01
50	1.56	9	1.71
63	1.83	9	2.01
80	3.25	9	3.57
100	4.48	7	4.82
125	6.90	0	6.90


\* At 100 stroke

## Applicable speed/load

- Piston speed: Max. 1000 mm/s (ø32 to ø125)
- Load yield: See table below.

Bore size [mm]	Maximum load mass [kg]
32	80
40	140
50	190
63	310
80	500
100	800
125	1300

\* Speed: 200 mm/s



Mounting dimensions are the same as the current product.

No environmental hazardous substances used

Lead free bushing is used as sliding material. Compliant with EU RoHS directive.

Various switches such as compact auto switches and magnetic field resistant auto switches can be mounted.

Compact auto switches

- D-M9□
- D-A9□



Magnetic field resistant auto switches

- D-P3DW\*1
- D-P3DWA
- D-P4DW

\*1 ø32 only



## Series Variations

Series	Type	Cushion	Bore size [mm]								Built-in magnet	With rod boot	Page
			32	40	50	63	80	100	125				
Standard Single rod MB-Z	Double acting, Single rod	Rubber	●	●	●	●	●	●	●	●	●	●	5
		Air	●	●	●	●	●	●	●	●	●	●	
Standard Double rod MBW-Z	Double acting, Double rod	Rubber	●	●	●	●	●	●	●	●	●	●	15
		Air	●	●	●	●	●	●	●	●	●	●	
Non-rotating rod Single rod MBK-Z	Double acting, Single rod	Rubber	●	●	●	●	●	●	●	●	●	●	21
		Air	●	●	●	●	●	●	●	●	●	●	
Non-rotating rod Double rod MBKW-Z	Double acting, Double rod	Rubber	●	●	●	●	●	●	●	●	●	●	25
		Air	●	●	●	●	●	●	●	●	●	●	
With end lock MBB	Double acting, Single rod	Rubber	●	●	●	●	●	●	●	●	●	●	29
		Air	●	●	●	●	●	●	●	●	●	●	
Smooth Cylinder MBY-Z	Double acting, Single rod	Rubber	●	●	●	●	●	●	●	●	●	●	CAT.ES20-235
Low friction MB□Q	Use the new series "Smooth Cylinder MBY Series" to realize bi-directional low friction and low-speed operation. (Refer to the WEB catalog or "CAT.ES20-235" catalog.)												



# Combinations of Standard and Made to Order Specifications

## Series MB

● : Standard
◎ : Made to Order
○ : Special product (Please contact SMC for details.)
— : Not available

<div>● : Standard</div> <div>◎ : Made to Order</div> <div>○ : Special product (Please contact SMC for details.)</div> <div>— : Not available</div>		Series	MB-Z (Standard type)									
		Action/ Type	Double acting									
			Single rod				Double rod					
		Cushion Page	Air		Rubber		Air		Rubber			
			5				15					
Symbol	Specifications	Applicable bore size	ø32 to ø100	ø125	ø32 to ø100	ø125	ø32 to ø100	ø125	ø32 to ø100	ø125		
Standard	Standard	ø32 to ø125	●	●	●	●	●	●	●	●		
Long st	Long stroke		●	●	●	●	●	●	●	●		
D	Built-in magnet		●	●	●	●	●	●	●	●		
MB□-□ <sup>J</sup> <sub>K</sub>	With rod boot		●	●	●	●	●	●	●	●		
25A	Copper (Cu) and Zinc (Zn)-free <sup>Note 1)</sup>	ø32 to ø100	●	○	○	○	○	○	○	○		
MB□ <sup>R</sup> <sub>V</sub>	Water resistant	ø32 to ø125	●	○	●	○	●	○	●	○		
10-	Clean series <sup>Note 6)</sup>		○	○	○	○	○	○	○	○		
20-	Copper <sup>Note 5)</sup> and Fluorine-free <sup>Note 6)</sup>		— <sup>Note 9)</sup>	— <sup>Note 9)</sup>	— <sup>Note 9)</sup>	— <sup>Note 9)</sup>	— <sup>Note 9)</sup>	— <sup>Note 9)</sup>	— <sup>Note 9)</sup>	— <sup>Note 9)</sup>		
XA□	Change of rod end shape	ø32 to ø125	◎	◎	◎	◎	◎	◎	◎	◎		
XB5	Oversized rod cylinder <sup>Note 6)</sup>		◎	○	○	○	○	○	○	○		
XB6	Heat resistant cylinder (–10 to 150°C)		◎	◎	○	○	◎	○	○	○		
XB13	Low speed cylinder (5 to 50 mm/s) <sup>Note 6)</sup>		◎	○	◎	○	○	○	○	○		
XC3	Special port location <sup>Note 6)</sup> <sup>Note 7)</sup>		◎	○	◎	○	◎	○	◎	○		
XC4	With heavy duty scraper		◎	○	◎	○	◎	○	◎	○		
XC5	Heat resistant cylinder (–10 to 110°C)		◎	◎	○	○	◎	○	○	○		
XC6	Made of stainless steel <sup>Note 6)</sup>		—	◎	—	◎	—	○	—	○		
XC7	Tie-rod, cushion valve, tie-rod nut, etc. made of stainless steel		◎	○	◎	○	◎	○	◎	○		
XC8	Adjustable stroke cylinder/Adjustable extension type		◎	○	◎	○	—	—	—	—		
XC9	Adjustable stroke cylinder/Adjustable retraction type		◎	○	◎	○	—	—	—	—		
XC10	Dual stroke cylinder/Double rod type		◎	○	◎	○	—	—	—	—		
XC11	Dual stroke cylinder/Single rod type		◎	○	◎	○	—	—	—	—		
XC12	Tandem cylinder		◎	○	◎	○	○	○	○	○		
XC14	Change of trunnion bracket mounting position		◎	◎	◎	◎	◎	◎	◎	◎		
XC22	Fluororubber seal		◎	◎	○	○	◎	○	○	○		
XC26	With split pins for double clevis pin/double knuckle joint pin and flat washers	ø125	—	◎	—	◎	—	—	—	—		
XC27	Double clevis and double knuckle joint pins made of stainless steel	ø32 to ø125	◎	◎	◎	◎	—	—	—	—		
XC29	Double knuckle joint with spring pin		◎	○	◎	○	○	○	○	○		
XC30	Rod trunnion		◎	○	◎	○	◎	○	◎	○		
XC35	With coil scraper		◎	○	◎	○	◎	○	◎	○		
XC65	Made of stainless steel (Combination of XC7 and XC68)		◎	○	◎	○	○	○	◎	○		
XC68	Made of stainless steel (with hard chrome plated piston rod)		◎	○	◎	○	◎	○	◎	○		
XC88	Spatter resistant coil scraper, Lube-retainer, Grease for welding (Piston rod: Stainless steel 304)		◎	○	◎	○	◎	○	◎	○		
XC89	Spatter resistant coil scraper, Lube-retainer, Grease for welding (Piston rod: S45C)		◎	○	◎	○	◎	○	◎	○		
XC91	Spatter resistant coil scraper, Grease for welding (Piston rod: S45C)		◎	○	◎	○	◎	○	◎	○		
X1184	Cylinder with heat resistant reed auto switch (–10 to 120°C)		◎	○	○	○	○	○	○	○		

Note 1) For details, refer to the **WEB catalog**.

Note 2) For details about the smooth cylinder, refer to the **WEB catalog** or "CAT.ES20-235" catalog.

Note 3) Simple specials except XC14A and XC14B.

Note 4) XC10 specification for the MBK-Z series is the non-rotating type on both sides. For only one side, submit a special order request form.

Note 5) Copper-free for the externally exposed part.



Use the new series "Smooth Cylinder MBY Series" to realize bi-directional low friction and low-speed operation. (Refer to the **WEB catalog** or "CAT.ES20-235" catalog.)

	MBK-Z (Non-rotating rod type)				MBB <small>Note 6)</small> (With end lock)	MBY-Z <small>Note 2)</small> (Smooth Cylinder)	MB□Q <small>Note 6)</small> (Low friction type)		
	Double acting								
	Single rod		Double rod		Single rod	Single rod	Single rod		
	Air	Rubber	Air	Rubber	Air	— <small>Note 9)</small>	—		
	21		25		29	—	37		
	ø32 to ø100								Symbol
	●	●	●	●	●	●	●	Standard	
	○	○	○	○	○	○	○	Long st	
	●	●	●	●	●	●	●	D	
	●	●	●	●	●	○	○	MB□-□ <sup>J</sup> <sub>K</sub>	
	—	—	—	—	○	—	—	25A	
	—	—	—	—	○	—	○	MB□ <sup>R</sup> <sub>V</sub>	
	○	○	○	○	○	—	○	10-	
	—	—	—	—	○	—	—	20-	
	◎	◎	○	○	◎	◎	◎	XA□	
	○	○	○	○	○	○	○	XB5	
	○	○	○	○	○	—	—	XB6	
	○	○	○	○	○	—	—	XB13	
	◎	◎	◎	◎	○	○	◎	XC3	
	—	—	—	—	○	—	—	XC4	
	○	○	○	○	○	—	—	XC5	
	◎ <small>Note 8)</small>	◎ <small>Note 8)</small>	◎	◎	○	—	◎	XC6	
	◎	◎	◎	◎	○	◎	◎	XC7	
	◎	◎	—	—	○	○	○	XC8	
	◎	◎	—	—	○	○	○	XC9	
	◎ <small>Note 4)</small>	◎ <small>Note 4)</small>	—	—	◎	○	○	XC10	
	○	○	—	—	○	○	○	XC11	
	○	○	○	○	○	—	—	XC12	
	◎	◎	○	○	◎ <small>Note 3)</small>	◎	◎	XC14	
	○	○	○	○	○	—	—	XC22	
	—	—	—	—	—	—	—	XC26	
	◎	◎	○	○	◎	◎	◎	XC27	
	○	○	○	○	◎	◎	◎	XC29	
	◎	◎	◎	◎	◎	◎	◎	XC30	
	—	—	—	—	○	—	○	XC35	
	—	—	—	—	○	◎	◎	XC65	
	—	—	—	—	—	◎	—	XC68	
	—	—	—	—	—	—	—	XC88	
	—	—	—	—	—	—	—	XC89	
	—	—	—	—	—	—	—	XC91	
	○	○	○	○	○	—	—	X1184	

Note 6) The cover shape is the same as the current product.

Note 7) The XC3BB, XC3CC and XC3DD with trunnion bracket are available with new models (part numbers with "Z").

Note 8) The piston rod of the MBK-Z series is made of stainless steel. The rod end nut made of stainless steel is available with X1292.

Note 9) The copper and fluorine-free specification is available as a standard product.

Standard	Double Acting, Single Rod	MB
Standard	Double Acting, Double Rod	MBW
Non-rotating Rod	Double Acting, Single Rod	MBK
Non-rotating Rod	Double Acting, Double Rod	MBKW
With End Lock		MBB
Low Friction		MB□Q
		Auto Switch
		Made to Order

# Air Cylinder: Standard Type Double Acting, Single Rod

## Series MB

ø32, ø40, ø50, ø63, ø80, ø100, ø125

RoHS

### How to Order



**MB B 32 - 50 Z - -**

**With auto switch** **MDB B 32 - 50 Z - M9BW -**

**With auto switch** (Built-in magnet)

**Mounting style**

B	Basic
L	Axial foot
F	Rod flange
G	Head flange
C	Single clevis
D	Double clevis
T	Center trunnion

\* Trunnion type is mounted before shipment.  
\* Other mounting brackets ø32 to ø100: Shipped together.  
ø125: Assembled before shipment.

**Bore size**

32	32 mm
40	40 mm
50	50 mm
63	63 mm
80	80 mm
100	100 mm
125	125 mm

**Accessories 1**

Nil	No bracket
N	Pivot bracket

\* Only for D and T mounting styles.  
\* Pivot bracket is shipped together with the product.  
\* For details, refer to page 13.

**Auto switch**

Nil	Without auto switch
-----	---------------------

\* For applicable auto switches, refer to the table below.

**Number of auto switches**

Nil	2 pcs.
S	1 pc.
3	3 pcs.
n	"n" pcs.

**Made to Order**  
For details, refer to page 6.

**Port thread type**

Nil	Rc
TN	NPT
TF	G

**Cylinder stroke [mm]**  
Refer to "Standard Strokes" on page 6.

**Suffix (Cushion)**

Nil	Air cushion
N*	Rubber bumper

\* Since the bumpers are attached to the both sides of the piston for rubber bumper type, the overall length is longer than the cylinder with air cushion as follows: ø32, ø40: +6 mm, ø50, ø63: +8 mm, ø80, ø100: +10 mm, ø125: +12 mm.

**Accessories 2**

Nil	No bracket
V	Single knuckle joint
W	Double knuckle joint

\* A knuckle joint pin is not provided with the single knuckle joint.  
\* Rod end bracket is shipped together with the product.

**Suffix (Rod boot)**

Nil	None
J	Nylon tarpaulin
K	Heat resistant tarpaulin

\* Refer to "Ordering Example of Cylinder Assembly" on page 6.

**Applicable Auto Switches**/Refer to the **WEB catalog** or the Best Pneumatics No. 2 for further information on auto switches.

Type	Special function	Electrical entry	Indicator/light	Wiring (Output)	Load voltage		Auto switch model		Lead wire length [m]				Pre-wired connector	Applicable load						
					DC	AC	Tie-rod mounting	Band mounting	0.5 (Nil)	1 (M)	3 (L)	5 (Z)								
Solid state auto switch	—	Grommet	Yes	3-wire (NPN)	24 V	5 V, 12 V	—	M9N	—	●	●	●	○	○	IC circuit	Relay, PLC				
		3-wire (PNP)		M9P				—	●	●	●	○	○							
	2-wire	M9B		—				●	●	●	○	○								
	Terminal conduit	3-wire (NPN)		24 V	5 V, 12 V	—		G39	—	—	—	—	—							
		2-wire				—			K39	—	—	—		—						
	Diagnostic indication (2-color indication)	Grommet				3-wire (NPN)		24 V	5 V, 12 V	M9NW	—	●	●	●	○		○	IC circuit		
				3-wire (PNP)	M9PW	—				●	●	●	○	○						
				2-wire	M9BW	—				●	●	●	○	○	—					
				3-wire (NPN)	M9NA*1	—				○	○	●	○	○	IC circuit					
	Water resistant (2-color indication)	3-wire (PNP)		M9PA*1	—	○		○	●	○	○	○								
		2-wire		M9BA*1	—	○		○	●	○	○	○	—							
	With diagnostic output (2-color indication)	Grommet		4-wire (NPN)	24 V	5 V, 12 V		F59F	—	●	—	●	○	○	IC circuit					
				2-wire (Non-polar)				—	P3DWA***	—	●	—	●	●			○	—		
	P3DW***								—	●	—	●	●	○						
	P4DW								—	—	—	●	●	○						
	Reed auto switch	—		Grommet	Yes	3-wire (NPN equivalent)		24 V	12 V	100 V	A96	—	●	—	●		—	—	IC circuit	Relay, PLC
No			2-wire		24 V	12 V	A93				—	●	●	●	—	—				
Yes							100 V or less				A90	—	●	—	●	—	—	IC circuit		
No							100 V, 200 V				A54	—	●	—	●	●	—			
Terminal conduit		Yes		200 V or less			A64			—	●	—	●	—	—	—				
				—			—			A33	—	—	—	—	—					
				100 V, 200 V			—			A34	—	—	—	—	—					
			—	—	A44	—	—			—	—	—								
Diagnostic indication (2-color indication)		Grommet	—	—	A59W	—	●			—	●	—	—	—	Relay, PLC					

\*1 Water resistant type auto switches can be mounted on the above models, but in such case SMC cannot guarantee water resistance.

A water resistant type cylinder is recommended for use in an environment which requires water resistance.

\* Lead wire length symbols: 0.5 m.....Nil (Example) M9NW 3 m.....L (Example) M9NWL  
1 m.....M (Example) M9NWM 5 m.....Z (Example) M9NWZ

\* Solid state auto switches marked with "○" are produced upon receipt of order.

\* Since there are other applicable auto switches than listed above, refer to page 45 for details.

\* For details about auto switches with pre-wired connector, refer to the **WEB catalog** or the Best Pneumatics No. 2.

For the D-P3DWA□, refer to the **WEB catalog**.

\* The D-A9□/M9□□□/P3DWA□ auto switches are shipped together, (but not assembled). (However, auto switch mounting brackets are assembled for the D-A9□/M9□□□ before shipment.)


\*\*\* The D-P3DWA cannot be mounted on ø32. Use the D-P3DW.

# Air Cylinder: Standard Type Double Acting, Single Rod **Series MB**



## Symbol

Double acting



## Made to Order

(For details, refer to pages 47 to 63.)

Symbol	Specifications
-XA□	Change of rod end shape
-XB5	Oversized rod cylinder*1 *2 *3
-XB6	Heat resistant cylinder (-10 to 150°C)
-XC3	Special port location*3
-XC4	With heavy duty scraper
-XC5	Heat resistant cylinder (-10 to 110°C)
-XC6	Made of stainless steel*3 *4
-XC7	Tie-rod, cushion valve, tie-rod nut, etc. made of stainless steel
-XC8	Adjustable stroke cylinder/Adjustable extension type
-XC9	Adjustable stroke cylinder/Adjustable retraction type
-XC10	Dual stroke cylinder/Double rod type
-XC11	Dual stroke cylinder/Single rod type
-XC12	Tandem cylinder
-XC14	Change of trunnion bracket mounting position
-XC22	Fluororubber seal
-XC26	With split pins for double clevis pin/double knuckle joint pin and flat washers*4
-XC27	Double clevis and double knuckle joint pins made of stainless steel
-XC29	Double knuckle joint with spring pin
-XC30	Rod trunnion
-XC35	With coil scraper
-XC65	Made of stainless steel (Combination of XC7 and XC68)*2
-XC68	Made of stainless steel (with hard chrome plated piston rod)*2
-XC88	Spatter resistant coil scraper, Lube-retainer, Grease for welding (Piston rod: Stainless steel 304)
-XC89	Spatter resistant coil scraper, Lube-retainer, Grease for welding (Piston rod: S45C)
-XC91	Spatter resistant coil scraper, Grease for welding (Piston rod: S45C)
-X1184	Cylinder with heat resistant reed auto switch (-10 to 120°C)

\*1 Air cushion only

\*2 Except ø125

\*3 The cover shape is the same as the current product.

\*4 ø125 only

For special port location (-XC3), the mounting bracket and port location can be determined using the standard product corresponding to the operating conditions. Also, this is only applicable to -XC3BB, -XC3CC and -XC3DD with trunnion bracket.

For parts made of stainless steel (-XC6), use the same specification stainless steel with the surface treatment (with hard chrome plated piston rod) (-XC68).

## Specifications

Bore size [mm]	32	40	50	63	80	100	125
Action	Double acting, Single rod						
Fluid	Air						
Proof pressure	1.5 MPa						
Maximum operating pressure	1.0 MPa						
Minimum operating pressure	0.05 MPa						
Ambient and fluid temperature	Without auto switch: -10 to 70°C With auto switch: -10 to 60°C (No freezing)						
Lubricant	Not required (Non-lube)						
Piston speed	50 to 1000 mm/s						
Stroke length tolerance	Up to 250: $\begin{smallmatrix} +1.0 \\ 0 \end{smallmatrix}$ , 251 to 1000: $\begin{smallmatrix} +1.4 \\ 0 \end{smallmatrix}$ , 1001 to 1500: $\begin{smallmatrix} +1.8 \\ 0 \end{smallmatrix}$ , 1501 to 2000: $\begin{smallmatrix} +2.2 \\ 0 \end{smallmatrix}$						
Cushion	Air cushion or Rubber bumper						
Port size (Rc)	1/8	1/4		3/8		1/2	
Mounting	Basic, Axial foot, Rod flange, Head flange Single clevis, Double clevis, Center trunnion						

## Standard Strokes

			[mm]
Bore size	Standard stroke		Max. manufacturable stroke
	Stroke range ①	Stroke range ②	
32	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500	Up to 1000	Up to 2700
40	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500	Up to 1800	
50	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600		
63	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600		
80	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600, 700, 800		
100	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600, 700, 800		
125	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600, 700, 800, 900, 1000	Up to 2000	

Note 1) Manufacture of intermediate strokes is possible. (Spacers are not used.)

Note 2) Applicable strokes should be confirmed according to the usage. For details, refer to "Air Cylinders Model Selection" on front matter pages of the Best Pneumatics No. 2 or the **WEB catalog**. In addition, the products that exceed the stroke range ① might not be able to fulfill the specifications due to the deflection etc.

Note 3) Please consult with SMC for manufacturability and the part numbers when exceeding the stroke range ②.

Note 4) The stroke range with rod boot is up to 1000 mm. Please consult with SMC when exceeding 1000 mm strokes.

## Ordering Example of Cylinder Assembly

**Cylinder model: MDBD32-50Z-NW-M9BW**

**Mounting D: Double clevis**  
**Pivot bracket N: Yes**  
**Rod end bracket W: Double knuckle joint**  
**Auto switch D-M9BW: 2 pcs.**

\* Pivot bracket, double knuckle joint and auto switch are shipped together with the product, but not assembled.

Refer to pages 38 to 45 for cylinders with auto switches.

- Auto switch proper mounting position (detection at stroke end) and its mounting height
- Minimum stroke for auto switch mounting
- Auto switch mounting brackets/Part no.
- Operating range



# Series MB

## Accessories

Mounting		Basic	Axial foot	Rod flange	Head flange	Single clevis	Double clevis	Center trunnion
Standard	Rod end nut	●	●	●	●	●	●	●
	Clevis pin	—	—	—	—	—	●	—
Option	Single knuckle joint	●	●	●	●	●	●	●
	Double knuckle joint (with pin)	●	●	●	●	●	●	●
	Rod boot	●	●	●	●	●	●	●

\* Refer to page 14 for dimensions and part numbers. (Except rod boot)

## Mounting Brackets/Part No.


Bore size [mm]	32	40	50	63	80	100	125
Axial foot <small>Note 1)</small>	MB-L03	MB-L04	MB-L05	MB-L06	MB-L08	MB-L10	MB-L12
Rod/Head flange	MB-F03	MB-F04	MB-F05	MB-F06	MB-F08	MB-F10	MB-F12
Single clevis	MB-C03	MB-C04	MB-C05	MB-C06	MB-C08	MB-C10	MB-C12
Double clevis	MB-D03	MB-D04	MB-D05	MB-D06	MB-D08	MB-D10	MB-D12

Note 1) Order two feet per cylinder.

Note 2) Accessories for each mounting bracket are as follows.

Axial foot, Rod/Head flange, Single clevis/Body mounting bolt; Double clevis/Body mounting bolt, Clevis pin, Flat washers and Split pins. → Refer to page 14 for details.

## Theoretical Force

(Unit: N) 

Bore size [mm]	Rod diameter [mm]	Operating direction	Piston area [mm <sup>2</sup> ]	Operating pressure [MPa]								
				0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
32	12	OUT	804	161	241	322	402	482	563	643	724	804
		IN	691	138	207	276	346	415	484	553	622	691
40	16	OUT	1257	251	377	503	629	754	880	1006	1131	1257
		IN	1056	211	317	422	528	634	739	845	950	1056
50	20	OUT	1963	393	589	785	982	1178	1374	1570	1767	1963
		IN	1649	330	495	660	825	989	1154	1319	1484	1649
63	20	OUT	3117	623	935	1247	1559	1870	2182	2494	2805	3117
		IN	2803	561	841	1121	1402	1682	1962	2242	2523	2803
80	25	OUT	5027	1005	1508	2011	2514	3016	3519	4022	4524	5027
		IN	4536	907	1361	1814	2268	2722	3175	3629	4082	4536
100	30	OUT	7854	1571	2356	3142	3927	4712	5498	6283	7069	7854
		IN	7147	1429	2144	2859	3574	4288	5003	5718	6432	7147
125	32	OUT	12272	2454	3682	4909	6136	7363	8590	9818	11045	12272
		IN	11468	2294	3440	4588	5734	6881	8028	9174	10321	11468

Note) Theoretical force [N] = Pressure [MPa] x Piston area [mm<sup>2</sup>]

## Weights


Bore size [mm]		32	40	50	63	80	100	125
Basic weight	Basic	0.44	0.59	1.04	1.29	2.41	3.36	5.48
	Axial foot	0.56	0.73	1.26	1.57	2.91	4.02	7.56
	Rod/Head flange	0.73	0.96	1.49	2.08	3.86	6.67	9.64
	Single clevis	0.69	0.82	1.38	1.92	3.52	6.53	8.05
	Double clevis	0.7	0.86	1.47	2.08	3.81	7.05	8.25
	Center trunnion	0.73	0.95	1.52	2.09	3.96	7.03	8.46
Additional weight per 50 mm of stroke		All mounting brackets	0.11	0.16	0.26	0.27	0.42	0.71
Accessories	Single knuckle joint	0.15	0.23	0.26	0.26	0.60	0.83	1.08
	Double knuckle joint (with pin)	0.22	0.37	0.43	0.43	0.87	1.27	1.58

## Rod Boot Material

Symbol	Material	Max. ambient temp.
J	Nylon tarpaulin	70°C
K	Heat resistant tarpaulin	110°C*

\* Max. ambient temperature for rod boot itself.

## Allowable Kinetic Energy



Example) Load limit at rod end when the air cylinder ø63 is actuated at 500 mm/s.

Extend upward from 500 mm/s on the horizontal axis of the graph to the intersection point with the line for a tube bore size of 63 mm, and then extend leftward from this point to find the load of 80 kg.

Calculation

Example) **MBB32-100Z** (Basic, ø32, 100 stroke)


• Basic weight..... 0.44 (Basic, ø32)

• Additional weight..... 0.11/50 stroke

• Cylinder stroke..... 100 stroke

0.44 + 0.11 x 100/50 = **0.66 kg**

## Construction



MB125

## Component Parts

No.	Description	Material	Q'ty	Note
1	Rod cover	Aluminum die-cast	1	Trivalent chromated
2	Head cover	Aluminum die-cast	1	Trivalent chromated
3	Cylinder tube	Aluminum alloy	1	Hard anodized
4	Piston rod	Carbon steel	1	Hard chrome plating
5	Piston	Aluminum alloy	1	
6	Cushion ring	Aluminum alloy	1	Anodized
7	Cushion ring B	Aluminum alloy	1	Anodized
8	Bushing	Bearing alloy	1	
9	Cushion valve	Steel wire	2	Trivalent zinc chromated
10	Retaining ring	Steel for spring	2	ø40 to ø125

No.	Description	Material	Q'ty	Note
11	Tie-rod	Carbon steel	4	Trivalent zinc chromated
12	Tie-rod nut	Carbon steel	8	Trivalent zinc chromated
13	Wear ring	Resin	1	
14	Rod seal	NBR	1	
15	Piston seal	NBR	1	
16	Cushion seal	Urethane	2	
17	Cushion valve seal	NBR	2	
18	Cylinder tube gasket	NBR	2	
19	Rod end nut	Rolled steel	1	Trivalent zinc chromated
20	Magnet	—	(1)	

## Replacement Parts/Seal Kit

Bore size [mm]	Kit no.	Contents
32	MB32Z-PS	Set of the nos. ⑭, ⑮, ⑯, ⑰
40	CA2-40Z-PS	
50	CA2-50Z-PS	
63	CA2-63Z-PS	
80	CA2-80Z-PS	
100	CA2-100Z-PS	
125	MB125-PS	

- \* Seal kits consist of items ⑭, ⑮, ⑯, ⑰, and can be ordered by using the seal kit number corresponding to each bore size.
  - \* Center trunnion type should not be disassembled. (Refer to page 64.)
  - \* The seal kit includes a grease pack (10 g for ø32 to ø50, 20 g for ø63 and ø80, 30 g for ø100 and ø125).
- Order with the following part number when only the grease pack is needed.  
Grease pack part number: GR-S-010 (10 g), GR-S-020 (20 g)


## Water Resistant Air Cylinder

Water resistant air cylinders are also available in the MB series, which are suitable for use on machine tools, where exposure to coolant is possible and applicable for food machinery and automobile washing equipment in an environment where water splashes. Please refer to the **WEB catalog** or the Best Pneumatics No. 2 for more information.


# Series MB

## Standard

### Basic: (B)



### With rod boot



Bore size [mm]	A	AL	B	B <sub>1</sub>	C	D	E	F	G	H	H <sub>1</sub>	J	K	KA	MA	MB	MM	N	P	S	TT	TX	TY	V	W	ZZ
32	22	19.5	46	17	32.5	12	30	13	13	47	6	M6 x 1	6	10	16	4	M10 x 1.25	27	1/8	84	17	48	49	4	6.5	135
40	30	27	52	22	38	16	35	13	14	51	8	M6 x 1	6	14	16	4	M14 x 1.5	27	1/4	84	22	55	58	4	9	139
50	35	32	65	27	46.5	20	40	14	15.5	58	11	M8 x 1.25	7	18	16	5	M18 x 1.5	31.5	1/4	94	22	68	71	5	10.5	156
63	35	32	75	27	56.5	20	45	14	16.5	58	11	M8 x 1.25	7	18	16	5	M18 x 1.5	31.5	3/8	94	28	81	81	9	12	156
80	40	37	95	32	72	25	45	20	19	72	13	M10 x 1.5	10	22	16	5	M22 x 1.5	38	3/8	114	34	102	102	11.5	14	190
100	40	37	114	41	89	30	55	20	19	72	16	M10 x 1.5	10	26	16	5	M26 x 1.5	38	1/2	114	40	124	124	17	15	190
125	54	50	136	41	110	32	60	27	19	97	16	M12 x 1.75	13	27	20	6	M27 x 2	38	1/2	120	50	148	148	17	15	223

### With Rod Boot

Bore size [mm]	d	e	f	ℓ											
				1 to 50	51 to 100	101 to 150	151 to 200	201 to 300	301 to 400	401 to 500	501 to 600	601 to 700	701 to 800	801 to 900	901 to 1000
32	54	36	23	12.5	25	37.5	50	75	100	125	—	—	—	—	—
40	56	41	23	12.5	25	37.5	50	75	100	125	—	—	—	—	—
50	64	51	25	12.5	25	37.5	50	75	100	125	150	—	—	—	—
63	64	51	25	12.5	25	37.5	50	75	100	125	150	—	—	—	—
80	68	56	29	12.5	25	37.5	50	75	100	125	150	175	200	—	—
100	76	61	29	12.5	25	37.5	50	75	100	125	150	175	200	—	—
125	82	75	27	10	20	30	40	60	80	100	120	140	160	180	200

Bore size [mm]	h												[mm]		Rubber Bumper	
	1 to 50	51 to 100	101 to 150	151 to 200	201 to 300	301 to 400	401 to 500	501 to 600	601 to 700	701 to 800	801 to 900	901 to 1000			S	ZZ
32	73	86	98	111	136	161	186	—	—	—	—	—			32	141
40	81	94	106	119	144	169	194	—	—	—	—	—			40	145
50	89	102	114	127	152	177	202	227	—	—	—	—			50	164
63	89	102	114	127	152	177	202	227	—	—	—	—			63	164
80	101	114	126	139	164	189	214	239	264	289	—	—			80	200
100	101	114	126	139	164	189	214	239	264	289	—	—			100	200
125	120	130	140	150	170	190	210	230	250	270	290	310			125	235


\* Model without air cushion is designed to include rubber bumpers. Since the bumpers are attached to the both sides of the piston, the overall length is longer than the cylinder with air cushion as follows: ø32, ø40: +6 mm, ø50, ø63: +8 mm, ø80, ø100: +10 mm, ø125: +12 mm



## Standard/With Mounting Bracket

\* Refer to Basic (B) for other dimensions.

### Axial foot: (L)




Bore size [mm]	LD	LH	LS	LT	LX	LY	LZ	TT	TX	TY	X	Y	ZZ
32	7	30	128	3.2	32	53	50	17	48	49	22	9	162
40	9	33	132	3.2	38	59	55	22	55	58	24	11	170
50	9	40	148	3.2	46	72.5	70	22	68	71	27	11	190
63	12	45	148	3.6	56	82.5	80	28	81	81	27	14	193
80	12	55	174	4.5	72	102.5	100	34	102	102	30	14	230
100	14	65	178	4.5	89	122	120	40	124	124	32	16	234
125	14	81	210	8	90	149	136	50	148	148	45	20	282

### Rubber Bumper

Bore size [mm]	LS	ZZ
32	134	168
40	138	176
50	156	198
63	156	201
80	184	240
100	188	244
125	222	294


\* Model without air cushion is designed to include rubber bumpers.  
Since the bumpers are attached to the both sides of the piston, the overall length is longer than the cylinder with air cushion as follows: ø32, ø40: +6 mm, ø50, ø63: +8 mm, ø80, ø100: +10 mm, ø125: +12 mm

### Rod flange: (F)



Bore size [mm]	FB	FD	FE	FT	FX	FY	FZ	Fd	TT	TX	TY
32	50	7	3	10	64	32	79	24.5	17	48	49
40	55	9	3	10	72	36	90	29.5	22	55	58
50	70	9	2	12	90	45	110	35.5	22	68	71
63	80	9	2	12	100	50	120	38.5	28	81	81
80	100	12	4	16	126	63	153	41	34	102	102
100	120	14	4	16	150	75	178	46	40	124	124
125	138	14	7	20	180	102	216	57	50	148	148

\* Model without air cushion is designed to include rubber bumpers.  
Since the bumpers are attached to the both sides of the piston, the overall length is longer than the cylinder with air cushion as follows: ø32, ø40: +6 mm, ø50, ø63: +8 mm, ø80, ø100: +10 mm, ø125: +12 mm





Standard	Double Acting, Single Rod	<b>MB</b>
Standard	Double Acting, Double Rod	<b>MBW</b>
Non-rotating Rod	Double Acting, Single Rod	<b>MBK</b>
Non-rotating Rod	Double Acting, Double Rod	<b>MBKW</b>
With End Lock		<b>MBB</b>
Low Friction		<b>MB□Q</b>
	Auto Switch	
	Made to Order	

## Standard/With Mounting Bracket

\* Refer to Basic (B) for other dimensions.

### Head flange: (G)





Bore size [mm]	FB	FD	FT	FX	FY	FZ	TT	TX	TY	ZZ
32	50	7	10	64	32	79	17	48	49	141
40	55	9	10	72	36	90	22	55	58	145
50	70	9	12	90	45	110	22	68	71	164
63	80	9	12	100	50	120	28	81	81	164
80	100	12	16	126	63	153	34	102	102	202
100	120	14	16	150	75	178	40	124	124	202
125	138	14	20	180	102	216	50	148	148	237

### Rubber Bumper

Bore size [mm]	ZZ
32	147
40	151
50	172
63	172
80	212
100	212
125	249

\* Model without air cushion is designed to include rubber bumpers. Since the bumpers are attached to the both sides of the piston, the overall length is longer than the cylinder with air cushion as follows: ø32, ø40: +6 mm, ø50, ø63: +8 mm, ø80, ø100: +10 mm, ø125: +12 mm

### Single clevis: (C)



Bore size [mm]	CDH10	CX	L	RR	TT	TX	TY	U	Z	ZZ
32	10 <sup>+0.058</sup> <sub>0</sub>	14 <sup>-0.1</sup> <sub>-0.3</sub>	23	10.5	17	48	49	13	154	164.5
40	10 <sup>+0.058</sup> <sub>0</sub>	14 <sup>-0.1</sup> <sub>-0.3</sub>	23	11	22	55	58	13	158	169
50	14 <sup>+0.070</sup> <sub>0</sub>	20 <sup>-0.1</sup> <sub>-0.3</sub>	30	15	22	68	71	17	182	197
63	14 <sup>+0.070</sup> <sub>0</sub>	20 <sup>-0.1</sup> <sub>-0.3</sub>	30	15	28	81	81	17	182	197
80	22 <sup>+0.084</sup> <sub>0</sub>	30 <sup>-0.1</sup> <sub>-0.3</sub>	42	23	34	102	102	26	228	251
100	22 <sup>+0.084</sup> <sub>0</sub>	30 <sup>-0.1</sup> <sub>-0.3</sub>	42	23	40	124	124	26	228	251
125	25 <sup>+0.084</sup> <sub>0</sub>	32 <sup>-0.1</sup> <sub>-0.3</sub>	50	28	50	148	148	30	267	295

### Rubber Bumper


Bore size [mm]	Z	ZZ
32	160	170.5
40	164	175
50	190	205
63	190	205
80	238	261
100	238	261
125	279	307

\* Model without air cushion is designed to include rubber bumpers. Since the bumpers are attached to the both sides of the piston, the overall length is longer than the cylinder with air cushion as follows: ø32, ø40: +6 mm, ø50, ø63: +8 mm, ø80, ø100: +10 mm, ø125: +12 mm

## Standard/With Mounting Bracket

\* Refer to Basic (B) for other dimensions.

### Double clevis: (D)




Bore size [mm]	CDH10	CDd9	CX	CZ	L	RR	TT	TX	TY	U	Z	ZZ
32	10 <sup>+0.058</sup> <sub>0</sub>	10 <sup>-0.040</sup> <sub>-0.076</sub>	14 <sup>+0.3</sup> <sub>+0.1</sub>	28	23	10.5	17	48	49	13	154	164.5
40	10 <sup>+0.058</sup> <sub>0</sub>	10 <sup>-0.04</sup> <sub>-0.076</sub>	14 <sup>+0.3</sup> <sub>+0.1</sub>	28	23	11	22	55	58	13	158	169
50	14 <sup>+0.070</sup> <sub>0</sub>	14 <sup>-0.050</sup> <sub>-0.093</sub>	20 <sup>+0.3</sup> <sub>+0.1</sub>	40	30	15	22	68	71	17	182	197
63	14 <sup>+0.070</sup> <sub>0</sub>	14 <sup>-0.050</sup> <sub>-0.093</sub>	20 <sup>+0.3</sup> <sub>+0.1</sub>	40	30	15	28	81	81	17	182	197
80	22 <sup>+0.084</sup> <sub>0</sub>	22 <sup>-0.065</sup> <sub>-0.117</sub>	30 <sup>+0.3</sup> <sub>+0.1</sub>	60	42	23	34	102	102	26	228	251
100	22 <sup>+0.084</sup> <sub>0</sub>	22 <sup>-0.065</sup> <sub>-0.117</sub>	30 <sup>+0.3</sup> <sub>+0.1</sub>	60	42	23	40	124	124	26	228	251
125	25 <sup>+0.084</sup> <sub>0</sub>	25 <sup>-0.065</sup> <sub>-0.117</sub>	32 <sup>+0.3</sup> <sub>+0.1</sub>	64	50	28	50	148	148	30	267	295

### Rubber Bumper

Bore size [mm]	Z	ZZ
32	160	170.5
40	164	175
50	190	205
63	190	205
80	238	261
100	238	261
125	279	307

\* Model without air cushion is designed to include rubber bumpers.  
Since the bumpers are attached to the both sides of the piston, the overall length is longer than the cylinder with air cushion as follows: ø32, ø40: +6 mm, ø50, ø63: +8 mm, ø80, ø100: +10 mm, ø125: +12 mm

### Center trunnion: (T)




Bore size [mm]	TD <sub>e8</sub>	TT	TX	TY	TZ	Z
32	12 <sup>-0.032</sup> <sub>-0.059</sub>	17	50	49	74	89
40	16 <sup>-0.032</sup> <sub>-0.059</sub>	22	63	58	95	93
50	16 <sup>-0.032</sup> <sub>-0.059</sub>	22	75	71	107	105
63	20 <sup>-0.040</sup> <sub>-0.073</sub>	28	90	87	130	105
80	20 <sup>-0.040</sup> <sub>-0.073</sub>	34	110	110	150	129
100	25 <sup>-0.040</sup> <sub>-0.073</sub>	40	132	136	182	129
125	25 <sup>-0.040</sup> <sub>-0.073</sub>	50	160	160	210	157

### Rubber Bumper

Bore size [mm]	Z
32	92
40	96
50	109
63	109
80	134
100	134
125	163

\* Model without air cushion is designed to include rubber bumpers.  
Since the bumpers are attached to the both sides of the piston, the "Z" dimension is longer than the cylinder with air cushion as follows: ø32, ø40: +3 mm, ø50, ø63: +4 mm, ø80, ø100: +5 mm, ø125: +6 mm



Standard	Double Acting, Single Rod	<b>MB</b>
Standard	Double Acting, Double Rod	<b>MBW</b>
Non-rotating Rod	Double Acting, Single Rod	<b>MBK</b>
Non-rotating Rod	Double Acting, Double Rod	<b>MBKW</b>
With End Lock		<b>MBB</b>
Low Friction		<b>MB□Q</b>
Auto Switch		<b>MB□Q</b>
Made to Order		<b>MB□Q</b>




## Pivot Bracket/Trunnion and Double Clevis Pivot Bracket

### Part No.

Bore size	MB□32	MB□40	MB□50	MB□63	MB□80	MB□100	MB□125
Description	MB-S03	MB-S04	MB-S04	MB-S06	MB-S06	MB-S10	MB-S12
Trunnion pivot bracket (Note)	MB-S03	MB-S04	MB-S04	MB-S06	MB-S06	MB-S10	MB-S12
Double clevis pivot bracket	MB-B03	MB-B05	MB-B05	MB-B08	MB-B08	MB-B12	MB-B12

Note) Order 2 trunnion pivot brackets per cylinder.

### Trunnion pivot bracket




Part no.	Bore size [mm]	B	TA	TL	TU	TC	TX	TE	TO	TR	TT	TS	TH	TF	Z**	TD <sub>H10</sub>
MB-S03	32	46	62	45	8.5	62	50	74	12	7	13	10	35	47	89	12 <sup>+0.070</sup> <sub>0</sub>
MB-S04	40	52	80	60	10	80	63	97	17	9	17	12	45	60	93	16 <sup>+0.070</sup> <sub>0</sub>
	50	65	80	60	10	92	75	109	17	9	17	12	45	60	105	16 <sup>+0.070</sup> <sub>0</sub>
MB-S06	63	75	100	70	15	110	90	130	20	11	22	14	60	80	105	20 <sup>+0.084</sup> <sub>0</sub>
	80	95	100	70	15	130	110	150	20	11	22	14	60	80	129	20 <sup>+0.084</sup> <sub>0</sub>
MB-S10	100	114	120	90	15	158	132	184	26	13.5	24	17	75	100	129	25 <sup>+0.084</sup> <sub>0</sub>
MB-S12	125	136	142	105	18.5	186	160	212	26	13.5	24	25	85	115	157	25 <sup>+0.084</sup> <sub>0</sub>

### Rubber Bumper

Bore size [mm]	Z
32	92
40	96
50	109
63	109
80	134
100	134
125	163

### Double clevis pivot bracket



Part no.	Bore size [mm]	B	DA	DB	DL	DU	DC	DX	DE	DO	DR	DT	DS	DH	Z*	DD <sub>H10</sub>
MB-B03	32	46	42	32	22	10	44	14	62	9	6.6	15	7	33	154	10 <sup>+0.058</sup> <sub>0</sub>
	40	52	42	32	22	10	44	14	62	9	6.6	15	7	33	158	10 <sup>+0.058</sup> <sub>0</sub>
MB-B05	50	65	53	43	30	11.5	60	20	81	10.5	9	18	8	45	182	14 <sup>+0.070</sup> <sub>0</sub>
	63	75	53	43	30	11.5	60	20	81	10.5	9	18	8	45	182	14 <sup>+0.070</sup> <sub>0</sub>
MB-B08	80	95	73	64	45	14	86	30	111	12.5	11	22	10	65	228	22 <sup>+0.084</sup> <sub>0</sub>
	100	114	73	64	45	14	86	30	111	12.5	11	22	10	65	228	22 <sup>+0.084</sup> <sub>0</sub>
MB-B12	125	136	90	78	60	15	110	32	136	13	13.5	24	14	75	267	25 <sup>+0.084</sup> <sub>0</sub>

### Rubber Bumper

Bore size [mm]	Z
32	160
40	164
50	190
63	190
80	238
100	238
125	279

### Rotating Angle

Bore size [mm]	A°	B°	A° + B° + 90°
32, 40	25°	45°	160°
50, 63	40°	60°	190°
80, 100	30°	55°	175°
125	30°	50°	170°

\*\* Model without air cushion is designed to include rubber bumpers.


Since the bumpers are attached to the both sides of the piston, the "Z" dimension is longer than the cylinder with air cushion as follows: ø32, ø40: +3 mm, ø50, ø63: +4 mm, ø80, ø100: +5 mm, ø125: +6 mm

\* Model without air cushion is designed to include rubber bumpers.

Since the bumpers are attached to the both sides of the piston, the overall length is longer than the cylinder with air cushion as follows: ø32, ø40: +6 mm, ø50, ø63: +8 mm, ø80, ø100: +10 mm, ø125: +12 mm


## Dimensions of Accessories

Rod end nut  
(Standard)



Part no.	Bore size [mm]	d	H	B	C	D
NT-03	32	M10 x 1.25	6	17	19.6	16.5
NT-04	40	M14 x 1.5	8	22	25.4	21
NT-05	50, 63	M18 x 1.5	11	27	31.2	26
NT-08	80	M22 x 1.5	13	32	37.0	31
NT-10	100	M26 x 1.5	16	41	47.3	39
NT-12M	125	M27 x 2	16	41	47.3	39

I type  
Single knuckle joint



Part no.	Bore size [mm]	A	A1	E1	L1	MM	R1	U1	NDH10	NX
I-03M	32	40	14	20	30	M10 x 1.25	12	16	10 <sup>+0.058</sup> <sub>0</sub>	14 <sup>+0.10</sup> <sub>-0.30</sub>
I-04M	40	50	19	22	40	M14 x 1.5	12.5	19	10 <sup>+0.058</sup> <sub>0</sub>	14 <sup>+0.10</sup> <sub>-0.30</sub>
I-05M	50, 63	64	24	28	50	M18 x 1.5	16.5	24	14 <sup>+0.070</sup> <sub>0</sub>	20 <sup>+0.10</sup> <sub>-0.30</sub>
I-08M	80	80	26	40	60	M22 x 1.5	23.5	34	22 <sup>+0.084</sup> <sub>0</sub>	30 <sup>+0.10</sup> <sub>-0.30</sub>
I-10M	100	80	26	40	60	M26 x 1.5	23.5	34	22 <sup>+0.084</sup> <sub>0</sub>	30 <sup>+0.10</sup> <sub>-0.30</sub>
I-12M	125	119	36	46	92	M27 x 2	28.5	34	25 <sup>+0.084</sup> <sub>0</sub>	32 <sup>+0.10</sup> <sub>-0.30</sub>


## Bracket Combinations

Bracket combination available ..... Refer to the figure below.

Bracket for cylinder	Bracket for workpiece	Single clevis	Double clevis	Single knuckle joint	Double knuckle joint	Clevis pivot bracket
Single clevis	—	—	①	—	②	—
Double clevis	③	—	—	④	—	⑨
Single knuckle joint	—	—	⑤	—	⑥	—
Double knuckle joint	⑦	—	—	⑧	—	⑩

No.	Appearance	No.	Appearance
①	Single clevis + Double clevis 	⑥	Single knuckle joint + Double knuckle joint 
②	Single clevis + Double knuckle joint 	⑦	Double knuckle joint + Single clevis 
③	Double clevis + Single clevis 	⑧	Double knuckle joint + Single knuckle joint 
④	Double clevis + Single knuckle joint 	⑨	Double clevis + Clevis pivot bracket 
⑤	Single knuckle joint + Double clevis 	⑩	Double knuckle joint + Clevis pivot bracket 


Knuckle joint pin  
Clevis pin



Part no.	Bore size [mm]	D <sub>d9</sub>	L	l	m	d	Applicable split pin
CD-M03 <sup>Note 1)</sup>	32, 40	10 <sup>+0.040</sup> <sub>-0.076</sub>	44	36	4	3	ø3 x 18 l
CD-M05 <sup>Note 1)</sup>	50, 63	14 <sup>+0.050</sup> <sub>-0.093</sub>	60	51	4.5	4	ø4 x 25 l
CD-M08 <sup>Note 1)</sup>	80, 100	22 <sup>+0.065</sup> <sub>-0.117</sub>	82	72	5	4	ø4 x 35 l
IY-12 <sup>Note 2)</sup>	125	25 <sup>+0.065</sup> <sub>-0.117</sub>	79.5	69.5	5	4	ø4 x 40 l

Note 1) Split pins and flat washers are included. Note 2) Only pins are included when shipped.

Y type  
Double knuckle joint



Part no.	Bore size [mm]	E1	L1	MM	R1	U1	NDH10	NX	NZ
Y-03M <sup>Note 1)</sup>	32	20	30	M10 x 1.25	10	16	10 <sup>+0.058</sup> <sub>0</sub>	14 <sup>+0.30</sup> <sub>-0.10</sub>	28 <sup>+0.10</sup> <sub>-0.30</sub>
Y-04M <sup>Note 1)</sup>	40	22	40	M14 x 1.5	11	19	10 <sup>+0.058</sup> <sub>0</sub>	14 <sup>+0.30</sup> <sub>-0.10</sub>	28 <sup>+0.10</sup> <sub>-0.30</sub>
Y-05M <sup>Note 1)</sup>	50, 63	28	50	M18 x 1.5	14	24	14 <sup>+0.070</sup> <sub>0</sub>	20 <sup>+0.30</sup> <sub>-0.10</sub>	40 <sup>+0.10</sup> <sub>-0.30</sub>
Y-08M <sup>Note 1)</sup>	80	40	65	M22 x 1.5	20	34	22 <sup>+0.084</sup> <sub>0</sub>	30 <sup>+0.30</sup> <sub>-0.10</sub>	60 <sup>+0.10</sup> <sub>-0.30</sub>
Y-10M <sup>Note 1)</sup>	100	40	65	M26 x 1.5	20	34	22 <sup>+0.084</sup> <sub>0</sub>	30 <sup>+0.30</sup> <sub>-0.10</sub>	60 <sup>+0.10</sup> <sub>-0.30</sub>
Y-12M <sup>Note 2)</sup>	125	46	100	M27 x 2	27	42	25 <sup>+0.084</sup> <sub>0</sub>	32 <sup>+0.30</sup> <sub>-0.10</sub>	64 <sup>+0.10</sup> <sub>-0.30</sub>

Note 1) A pin, split pins and flat washers are included. Note 2) A pin and split pins are included.

# Air Cylinder: Standard Type Double Acting, Double Rod

## Series MBW

ø32, ø40, ø50, ø63, ø80, ø100, ø125

RoHS

### How to Order



**MBW L 32 - 150 Z -**

**With auto switch** **MDBW L 32 - 150 Z - M9BW -**

**Mounting style**

B	Basic
L	Axial foot
F	Rod flange
T	Center trunnion

\* Trunnion type is mounted before shipment.  
\* Other mounting brackets ø32 to ø100: Shipped together.  
ø125: Assembled before shipment.

**Bore size**

32	32 mm
40	40 mm
50	50 mm
63	63 mm
80	80 mm
100	100 mm
125	125 mm

**Port thread type**

Nil	Rc
TN	NPT
TF	G

**Cylinder stroke [mm]**  
Refer to "Standard Strokes" on page 16.

**Auto switch**

Nil	Without auto switch
-----	---------------------

\* For applicable auto switches, refer to the table below.

**Number of auto switches**

Nil	2 pcs.
S	1 pc.
3	3 pcs.
n	"n" pcs.

**Made to Order**  
For details, refer to page 16.

**Suffix (Cushion)**

Nil	Air cushion
N*	Rubber bumper

\* Since the bumpers are attached to the both sides of the piston for rubber bumper type, the overall length is longer than the cylinder with air cushion as follows: ø32, ø40: +6 mm, ø50, ø63: +8 mm, ø80, ø100: +10 mm, ø125: +12 mm.

**Suffix (Rod boot)**

Nil	None
J	Nylon tarpaulin (one end)
JJ	Nylon tarpaulin (both ends)
K	Heat resistant tarpaulin (one end)
KK	Heat resistant tarpaulin (both ends)

**Applicable Auto Switches**/Refer to the **WEB catalog** or the Best Pneumatics No. 2 for further information on auto switches.

Type	Special function	Electrical entry	Indicator light	Wiring (Output)	Load voltage			Auto switch model		Lead wire length [m]					Pre-wired connector	Applicable load		
					DC		AC	Tie-rod mounting	Band mounting	0.5 (Nil)	1 (M)	3 (L)	5 (Z)					
Solid state auto switch	—	Grommet	Yes	3-wire (NPN)	24 V	5 V, 12 V	—	M9N	—	●	●	●	○	○	IC circuit	Relay, PLC		
				3-wire (PNP)				M9P	—	●	●	●	○	○				
				2-wire				M9B	—	●	●	●	○	○				
		Terminal conduit		3-wire (NPN)	24 V	5 V, 12 V	—	—	G39	—	—	—	—	—	—			
	2-wire			12 V				—	K39	—	—	—	—					
	Grommet	3-wire (NPN)		5 V, 12 V				—	M9NW	—	●	●	●	○	○		IC circuit	
		3-wire (PNP)			M9PW	—	●		●	●	○	○						
		2-wire			12V	M9BW	—		●	●	●	○	○	—				
		3-wire (NPN)		5 V, 12 V	—	M9NA*1	—	○	○	●	○	○	IC circuit					
		3-wire (PNP)				M9PA*1	—	○	○	●	○	○						
		2-wire				M9BA*1	—	○	○	●	○	○	—					
		Diagnostic output (2-color indication)		4-wire (NPN)	5 V, 12 V	—	F59F	—	●	—	●	○	○	IC circuit				
							P3DWA***	—	●	—	●	●	○		—			
	Magnetic field resistant (2-color indication)	2-wire (Non-polar)		—	—	P3DW***	—	●	—	●	●	○	—					
P4DW			—			—	—	●	●	○								
Reed auto switch	—	Grommet	Yes	3-wire (Equiv. to NPN)	24 V	5 V	—	A96	—	●	—	●	—	—	IC circuit	Relay, PLC		
			No	2-wire				12 V	100 V	A93	—	●	●	●	●		—	—
			Yes						100 V or less	A90	—	●	—	●	—		—	IC circuit
			No						100 V, 200 V	A54	—	●	—	●	●		—	
		Terminal conduit	200 V or less			A64	—		●	—	●	—	—	PLC				
			—			—	A33		—	—	—	—	—		PLC			
		DIN terminal	100 V, 200 V			—	A34		—	—	—	—	—	PLC				
			—	—		A44	—	—	—	—	—							
		Diagnostic indication (2-color indication)	Grommet	Yes		—	—	—	A59W	—	●	—	●	—	—			

\*1 Water resistant type auto switches can be mounted on the above models, but in such case SMC cannot guarantee water resistance.

Please contact SMC regarding water resistant types with the above model numbers.

\* Lead wire length symbols: 0.5 m..... Nil (Example) M9NW 3 m..... L (Example) M9NWL  
1 m..... M (Example) M9NWM 5 m..... Z (Example) M9NWX

\* Solid state auto switches marked with "○" are produced upon receipt of order.

\* Since there are other applicable auto switches than listed above, refer to page 45 for details.

\* For details about auto switches with pre-wired connector, refer to the **WEB catalog** or the Best Pneumatics No. 2.

For the D-P3DWA□, refer to the **WEB catalog**.

\* The D-A9□/M9□□□/P3DWA□ auto switches are shipped together, (but not assembled). (However, auto switch mounting brackets are assembled for the D-A9□/M9□□□ before shipment.)


\*\*\* The D-P3DWA cannot be mounted on ø32. Use the D-P3DW.





## Symbol

Double acting, Air cushion



## Made to Order

(For details, refer to pages 47 to 63.)

Symbol	Specifications
-XA□	Change of rod end shape
-XB6	Heat resistant cylinder (−10 to 150°C)
-XC3	Special port location*1 *2
-XC4	With heavy duty scraper
-XC5	Heat resistant cylinder (−10 to 110°C)
-XC7	Tie-rod, cushion valve, tie-rod nut, etc. made of stainless steel
-XC14	Change of trunnion bracket mounting position
-XC22	Fluororubber seal
-XC30	Rod trunnion
-XC35	With coil scraper
-XC68	Made of stainless steel (with hard chrome plated piston rod)*3
-XC88	Spatter resistant coil scraper, Lube-retainer, Grease for welding (Piston rod: Stainless steel 304)
-XC89	Spatter resistant coil scraper, Lube-retainer, Grease for welding (Piston rod: S45C)
-XC91	Spatter resistant coil scraper, Grease for welding (Piston rod: S45C)

\*1 The cover shape is the same as the current product.

\*2 ø125 only

\*3 Except ø125

For special port location (-XC3), the mounting bracket and port location can be determined using the standard product corresponding to the operating conditions. Also, this is only applicable to -XC3BB, -XC3CC and -XC3DD with trunnion bracket.

For parts made of stainless steel (-XC6), use the same specification stainless steel with the surface treatment (with hard chrome plated piston rod) (-XC68).

Refer to pages 38 to 45 for cylinders with auto switches.

- Auto switch proper mounting position (detection at stroke end) and its mounting height
- Minimum stroke for auto switch mounting
- Auto switch mounting brackets/Part no.
- Operating range

## Water Resistant Air Cylinder

Water resistant air cylinders are also available in the MB series, which are suitable for use on machine tools in an atmosphere with coolant and applicable to food machinery and automobile washing equipment in an environment with water splashes. Please refer to the **WEB catalog** or the Best Pneumatics No. 2 for more information.

## Specifications

Bore size [mm]	32	40	50	63	80	100	125
Action	Double acting, Double rod						
Fluid	Air						
Proof pressure	1.5 MPa						
Max. operating pressure	1.0 MPa						
Min. operating pressure	0.05 MPa						
Ambient and fluid temperature	Without auto switch: −10 to 70°C With auto switch: −10 to 60°C (No freezing)						
Lubrication	Not required (Non-lube)						
Operating piston speed	50 to 1000 mm/s						50 to 700 mm/s
Allowable stroke tolerance	Up to 250: $+1.0_0$ , 251 to 1000: $+1.4_0$ , 1001 to 1500						
Cushion <sup>Note</sup>	Air cushion or Rubber bumper						
Port size (Rc, NPT, G)	1/8	1/4		3/8		1/2	
Mounting	Basic, Axial foot, Rod flange, Center trunnion						

Note) Kinetic energy absorbable by the cushion mechanism is identical to double acting, single rod.

## Standard Strokes

Bore size	Standard stroke		Max. manufacturable stroke
	Stroke range ①	Stroke range ②	
32	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500	Up to 1000	Up to 1800
40	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500		
50	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600	Up to 1200	
63	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600		
80	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600, 700, 800	Up to 1500	
100	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600, 700, 800		
125	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600, 700, 800, 900, 1000		

Note 1) Manufacture of intermediate strokes is possible. (Spacers are not used.)

Note 2) Applicable strokes should be confirmed according to the usage. For details, refer to "Air Cylinders Model Selection" on front matter pages of the Best Pneumatics No. 2 or the **WEB catalog**. In addition, the products that exceed the stroke range ① might not be able to fulfill the specifications due to the deflection etc.

Note 3) Please consult with SMC for manufacturability and the part numbers when exceeding the stroke range ②.

Note 4) The stroke range with rod boot is up to 1000 mm. Please consult with SMC when exceeding 1000 mm strokes.

## Accessories

Mounting		Basic	Axial foot	Rod flange	Center trunnion
Standard	Rod end nut	●	●	●	●
	Single knuckle joint	●	●	●	●
	Double knuckle joint (with pin)	●	●	●	●
	Rod boot	●	●	●	●

\* Refer to page 14 for dimensions and part numbers. (Except rod boot)

## Rod Boot Material

Symbol	Material	Max. ambient temp.
J	Nylon tarpaulin	70°C
K	Heat resistant tarpaulin	110°C*

\* Max. ambient temperature for rod boot itself.

## Mounting Brackets/Part No.

Bore size [mm]	32	40	50	63	80	100	125
Axial foot	MB-L03	MB-L04	MB-L05	MB-L06	MB-L08	MB-L10	MB-L12
Rod flange	MB-F03	MB-F04	MB-F05	MB-F06	MB-F08	MB-F10	MB-F12

\* Order two foots per cylinder.

## Theoretical Force

(Unit: N) OUT ← IN →

Bore size [mm]	Rod diameter [mm]	Operating direction	Piston area [mm <sup>2</sup> ]	Operating pressure [MPa]								
				0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
<b>32</b>	12	IN, OUT	691	138	207	276	346	415	484	553	622	691
<b>40</b>	16	IN, OUT	1056	211	317	422	528	634	739	845	950	1056
<b>50</b>	20	IN, OUT	1649	330	495	660	825	989	1154	1319	1484	1649
<b>63</b>	20	IN, OUT	2803	561	841	1121	1402	1682	1962	2242	2523	2803
<b>80</b>	25	IN, OUT	4536	907	1361	1814	2268	2722	3175	3629	4082	4536
<b>100</b>	30	IN, OUT	7147	1429	2144	2859	3574	4288	5003	5718	6432	7147
<b>125</b>	32	IN, OUT	11468	2294	3440	4588	5734	6881	8028	9174	10321	11468

Note) Theoretical force [N] = Pressure [MPa] x Piston area [mm<sup>2</sup>]

## Weights/Aluminum Tube

[kg]

Bore size [mm]		32	40	50	63	80	100	125
Basic weight	Basic	0.56	0.78	1.37	1.64	3.05	4.23	6.48
	Axial foot	0.68	0.92	1.59	1.92	3.55	4.89	8.56
	Rod flange	0.85	1.15	1.82	2.43	4.50	7.54	10.64
	Center trunnion	0.85	1.14	1.85	2.44	4.60	7.90	9.46
Additional weight per 50 mm of stroke	All mounting brackets	0.15	0.24	0.37	0.38	0.61	0.82	1.02
Accessories	Single knuckle joint	0.15	0.23	0.26	0.26	0.60	0.83	1.08
	Double knuckle joint (with pin)	0.22	0.37	0.43	0.43	0.87	1.27	1.58


Calculation

Example) **MBWB32-100Z** (Basic, ø32, 100 stroke)

- Basic weight..... 0.56 (Basic, ø32)
- Additional weight..... 0.15/50 stroke
- Cylinder stroke..... 100 stroke

$$0.56 + 0.15 \times 100/50 = \mathbf{0.86 \text{ kg}}$$

## Construction



### Component Parts

No.	Description	Material	Q'ty	Note
1	Rod cover	Aluminum die-cast	2	Trivalent zinc chromated
2	Cylinder tube	Aluminum alloy	1	Hard anodized
3	Piston rod	Carbon steel	1	Hard chrome plating
4	Piston	Aluminum alloy	1	
5	Cushion ring	Aluminum alloy	2	Anodized
6	Bushing	Bearing alloy	2	
7	Cushion valve	Steel wire	2	Trivalent zinc chromated
8	Retaining ring	Steel for spring	2	ø40 to ø125
9	Tie-rod	Carbon steel	4	Trivalent zinc chromated

No.	Description	Material	Q'ty	Note
10	Tie-rod nut	Carbon steel	8	Trivalent zinc chromated
11	Rod seal	NBR	2	
12	Piston seal	NBR	1	
13	Cushion seal	Urethane	2	
14	Cushion valve seal	NBR	2	
15	Cylinder tube gasket	NBR	2	
16	Rod end nut	Rolled steel	2	Trivalent zinc chromated
17	Magnet	—	(1)	

### Replacement Parts/Seal Kit


Bore size [mm]	Kit no.	Contents
32	MBW32Z-PS	Set of the nos. ⑪, ⑫, ⑬, ⑮
40	CA2W40Z-PS	
50	CA2W50Z-PS	
63	CA2W63Z-PS	
80	CA2W80Z-PS	
100	CA2W100Z-PS	
125	MBW125-PS	

- \* Seal kits consist of items ⑪, ⑫, ⑬, ⑮, and can be ordered by using the seal kit number corresponding to each bore size.
- \* Trunnion type should not be disassembled. (Refer to page 64.)
- \* The seal kit includes a grease pack (10 g for ø32 to ø50, 20 g for ø63 and ø80, 30 g for ø100 and ø125).  
Order with the following part number when only the grease pack is needed.  
**Grease pack part number: GR-S-010 (10 g), GR-S-020 (20 g)**


# Series MBW

## Standard

### Basic: (B)



### With rod boot



### Rubber Bumper

Bore size [mm]	S	ZZ
32	90	184
40	90	192
50	102	218
63	102	218
80	124	268
100	124	268
125	132	326

Bore size [mm]	A	AL	B	B <sub>1</sub>	C	D	E	F	G	H	H <sub>1</sub>	J	K	KA	MA	MB	MM	N	P	S	TT	TX	TY	V	W	ZZ
32	22	19.5	46	17	32.5	12	30	13	13	47	6	M6 x 1	6	10	16	4	M10 x 1.25	27	1/8	84	17	48	49	4	6.5	178
40	30	27	52	22	38	16	35	13	14	51	8	M6 x 1	6	14	16	4	M14 x 1.5	27	1/4	84	22	55	58	4	9	186
50	35	32	65	27	46.5	20	40	14	15.5	58	11	M8 x 1.25	7	18	16	5	M18 x 1.5	31.5	1/4	94	22	68	71	5	10.5	210
63	35	32	75	27	56.5	20	45	14	16.5	58	11	M8 x 1.25	7	18	16	5	M18 x 1.5	31.5	3/8	94	28	81	81	9	12	210
80	40	37	95	32	72	25	45	20	19	72	13	M10 x 1.5	10	22	16	5	M22 x 1.5	38	3/8	114	34	102	102	11.5	14	258
100	40	37	114	41	89	30	55	20	19	72	16	M10 x 1.5	10	26	16	5	M26 x 1.5	38	1/2	114	40	124	124	17	15	258
125	54	50	136	41	110	32	60	27	19	97	16	M12 x 1.75	13	27	20	6	M27 x 2.0	38	1/2	120	50	148	148	17	15	314

### With Rod Boot

Bore size [mm]	d	e	f	ℓ																h											
				1 to 50	51 to 100	101 to 150	151 to 200	201 to 300	301 to 400	401 to 500	501 to 600	601 to 700	701 to 800	801 to 900	901 to 1000	1 to 50	51 to 100	101 to 150	151 to 200	201 to 300	301 to 400	401 to 500	501 to 600	601 to 700	701 to 800	801 to 900	901 to 1000				
32	54	36	23	12.5	25	37.5	50	75	100	125	—	—	—	—	—	73	86	98	111	136	161	186	—	—	—	—	—	—	—	—	—
40	56	41	23	12.5	25	37.5	50	75	100	125	—	—	—	—	—	81	94	106	119	144	169	194	—	—	—	—	—	—	—	—	—
50	64	51	25	12.5	25	37.5	50	75	100	125	150	—	—	—	—	89	102	114	127	152	177	202	227	—	—	—	—	—	—	—	—
63	64	51	25	12.5	25	37.5	50	75	100	125	150	—	—	—	—	89	102	114	127	152	177	202	227	—	—	—	—	—	—	—	—
80	68	56	29	12.5	25	37.5	50	75	100	125	150	175	200	—	—	101	114	126	139	164	189	214	239	264	289	—	—	—	—	—	—
100	76	61	29	12.5	25	37.5	50	75	100	125	150	175	200	—	—	101	114	126	139	164	189	214	239	264	289	—	—	—	—	—	—
125	82	75	27	10	20	30	40	60	80	100	120	140	160	180	200	120	130	140	150	170	190	210	230	250	270	290	310	—	—	—	—

Note) ZZ indicates dimensions for double side rod boot. [mm]



Bore size [mm]	ZZ Note)											
	1 to 50	51 to 100	101 to 150	151 to 200	201 to 300	301 to 400	401 to 500	501 to 600	601 to 700	701 to 800	801 to 900	901 to 1000
32	230	256	280	306	356	406	456	—	—	—	—	—
40	246	272	296	322	372	422	472	—	—	—	—	—
50	272	298	322	348	398	448	498	548	—	—	—	—
63	272	298	322	348	398	448	498	548	—	—	—	—
80	316	342	366	392	442	492	542	592	642	692	—	—
100	316	342	366	392	442	492	542	592	642	692	—	—
125	360	380	400	420	460	500	540	580	620	660	700	740

\* Model without air cushion is designed to include rubber bumpers. Since the bumpers are attached to the both sides of the piston, the overall length is longer than the cylinder with air cushion as follows: ø32, ø40: +6 mm, ø50, ø63: +8 mm, ø80, ø100: +10 mm, ø125: +12 mm

## Standard/With Mounting Bracket



\* Refer to Basic (B) for other dimensions and with rod boot.

### Axial foot: (L)





Bore size [mm]	X	Y	LD	LH	LS*	LT	LX	LY	LZ	TT	TX	TY
32	22	9	7	30	128	3.2	32	53	50	17	48	49
40	24	11	9	33	132	3.2	38	59	55	22	55	58
50	27	11	9	40	148	3.2	46	72.5	70	22	68	71
63	27	14	12	45	148	3.6	56	82.5	80	28	81	81
80	30	14	12	55	174	4.5	72	102.5	100	34	102	102
100	32	16	14	65	178	4.5	89	122	120	40	124	124
125	45	20	14	81	210	8	90	149	136	50	148	148

### Rod flange: (F)



Bore size [mm]	FB	FD	FT	FX	FY	FZ	Fd	TT	TX	TY
32	50	7	10	64	32	79	24.5	17	48	49
40	55	9	10	72	36	90	29.5	22	55	58
50	70	9	12	90	45	110	35.5	22	68	71
63	80	9	12	100	50	120	38.5	28	81	81
80	100	12	16	126	63	153	41	34	102	102
100	120	14	16	150	75	178	46	40	124	124
125	138	14	20	180	102	216	57	50	148	148

### Center trunnion: (T)



Bore size [mm]	TDe8	TT	TX	TY	TZ	Z**
32	12	17	50	49	74	89
40	16	22	63	58	95	93
50	16	22	75	71	107	105
63	20	28	90	87	130	105
80	20	34	110	110	150	129
100	25	40	132	136	182	129
125	25	50	160	160	210	157

\* Model without air cushion is designed to include rubber bumpers. Since the bumpers are attached to the both sides of the piston, the overall length is longer than the cylinder with air cushion as follows: ø32, ø40: +6 mm, ø50, ø63: +8 mm, ø80, ø100: +10 mm, ø125: +12 mm

\*\* Model without air cushion is designed to include rubber bumpers. Since the bumpers are attached to the both sides of the piston, the "Z" dimension is longer than the cylinder with air cushion as follows: ø32, ø40: +3 mm, ø50, ø63: +4 mm, ø80, ø100: +5 mm, ø125: +6 mm (For trunnion mounting)




# Air Cylinder: Non-rotating Rod Type Double Acting, Single Rod

## Series MBK

ø32, ø40, ø50, ø63, ø80, ø100

RoHS

### How to Order



**MBK B 32 - 50 Z - -**

**With auto switch** **MDBK B 32 - 50 Z - M9BW -**

**With auto switch**  
(Built-in magnet)

**Mounting style**

B	Basic/Without bracket
L	Axial foot
F	Rod flange
G	Head flange
C	Single clevis
D	Double clevis
T	Center trunnion

\* Mounting brackets other than trunnion type are shipped together.

**Bore size**

32	32 mm
40	40 mm
50	50 mm
63	63 mm
80	80 mm
100	100 mm

**Port thread type**

Nil	Rc
TN	NPT
TF	G

**Cylinder stroke [mm]**  
Refer to "Standard Strokes" on page 22.

**Accessories 1**

Nil	No bracket
N	Pivot bracket

\* Only for D and T mounting styles.  
\* Pivot bracket is shipped together with the product.  
\* For details, refer to page 13.

**Suffix (Cushion)**

Nil	Air cushion
N*	Rubber bumper

\* Since the bumpers are attached to the both sides of the piston for rubber bumper type, the overall length is longer than the cylinder with air cushion as follows: ø32, ø40: +6 mm, ø50, ø63: +8 mm, ø80, ø100: +10 mm.

**Suffix (Rod boot)**

Nil	None
J	Nylon tarpaulin
K	Heat resistant tarpaulin

**Auto switch**

Nil	Without auto switch
-----	---------------------

\* For applicable auto switches, refer to the table below.

**Number of auto switches**

Nil	2 pcs.
S	1 pc.
3	3 pcs.
n	"n" pcs.

**Made to Order**  
For details, refer to page 22.

**Accessories 2**

Nil	No bracket
V	Single knuckle joint
W	Double knuckle joint

\* A knuckle joint pin is not provided with the single knuckle joint.  
\* Rod end bracket is shipped together with the product.  
\* The screw-in amount of the piston rod end cannot be adjusted when a clevis bracket, trunnion bracket and knuckle joint are used together.

**Applicable Auto Switches**/Refer to the **WEB catalog** or the Best Pneumatics No. 2 for further information on auto switches.

Type	Special function	Electrical entry	Indicator light	Wiring (Output)	Load voltage		Auto switch model		Lead wire length [m]				Pre-wired connector	Applicable load		
					DC		AC	Tie-rod mounting	Band mounting	0.5 (Nil)	1 (M)	3 (L)		5 (Z)		
Solid state auto switch	—	Grommet	Yes	3-wire (NPN)	24 V	5 V, 12 V	—	M9N	—	●	●	●	○	○	IC circuit	Relay, PLC
		3-wire (PNP)		M9P				—	●	●	●	○	○			
		2-wire		M9B				—	●	●	●	○	○			
	Terminal conduit	3-wire (NPN)		24 V	5 V, 12 V	—	G39	—	—	—	—	—	—			
		2-wire					—	K39	—	—	—	—				
	Diagnostic indication (2-color indication)	Grommet		3-wire (NPN)	24 V	5 V, 12 V	—	M9NW	—	●	●	●	○	○	IC circuit	
				3-wire (PNP)				M9PW	—	●	●	●	○	○		
				2-wire				M9BW	—	●	●	●	○	○		
	Water resistant (2-color indication)		3-wire (NPN)	24 V	5 V, 12 V	M9NA*1		—	○	○	●	○	○	IC circuit		
			3-wire (PNP)			M9PA*1		—	○	○	●	○	○			
	2-wire		M9BA*1			—		○	○	●	○	○				
	Diagnostic output (2-color indication)		Grommet	4-wire (NPN)	24 V	5 V, 12 V		F59F	—	●	—	●	○	○	IC circuit	
				2-wire (Non-polar)				—	P3DWA***	—	●	—	●	●		
P3DW***	—	●			—	●	●		○	—						
P4DW	—	—		—	●	●	○									
Reed auto switch	—	Grommet	Yes	3-wire (Equiv. to NPN)	24 V	5 V	—	A96	—	●	—	●	—	—	IC circuit	Relay, PLC
				2-wire				100 V	A93	—	●	●	●	—	—	
								100 V or less	A90	—	●	—	●	—	—	
								100 V, 200 V	A54	—	●	—	●	—	—	
		200 V or less						A64	—	●	—	●	—	—		
		Terminal conduit		Yes				—	A33	—	—	—	—	—	—	
								100 V, 200 V	A34	—	—	—	—	—		
		DIN terminal		Yes				—	A44	—	—	—	—	—	—	
	—		A59W		—	●	—	●	—	—						
	Diagnostic indication (2-color indication)	Grommet	—	—	A59W	—	●	—	●	—	—	Relay, PLC				

\*1 Water resistant type auto switches can be mounted on the above models, but in such case SMC cannot guarantee water resistance.

A water resistant type cylinder is recommended for use in an environment which requires water resistance.

\* Lead wire length symbols: 0.5 m ..... Nil (Example) M9NW 3 m ..... L (Example) M9NWL  
1 m ..... M (Example) M9NWM 5 m ..... Z (Example) M9NWZ

\* Solid state auto switches marked with "○" are produced upon receipt of order.

\* Since there are other applicable auto switches than listed above, refer to page 45 for details.


\* For details about auto switches with pre-wired connector, refer to the **WEB catalog** or the Best Pneumatics No. 2.

For the D-P3DWA, refer to the **WEB catalog**.

\* The D-A9□/M9□□□/P3DWA□ auto switches are shipped together, (but not assembled). (However, auto switch mounting brackets are assembled for the D-A9□/M9□□□ before shipment.)


\*\*\* The D-P3DWA cannot be mounted on ø32. Use the D-P3DW.

# Air Cylinder: Non-rotating Rod Type Double Acting, Single Rod **Series MBK**



## Symbol

Double acting, Air cushion



## Made to Order

(For details, refer to pages 47 to 63.)

Symbol	Specifications
-XA□	Change of rod end shape
-XC3	Special port location*
-XC6	Made of stainless steel
-XC7	Tie-rod, cushion valve, tie-rod nut, etc. made of stainless steel
-XC8	Adjustable stroke cylinder/Adjustable extension type
-XC9	Adjustable stroke cylinder/Adjustable retraction type
-XC10	Dual stroke cylinder/Double rod type
-XC14	Change of trunnion bracket mounting position
-XC27	Double clevis and double knuckle joint pins made of stainless steel
-XC30	Rod trunnion

\* The cover shape is the same as the current product.

For special port location (-XC3), the mounting bracket and port location can be determined using the standard product corresponding to the operating conditions. Also, this is only applicable to -XC3BB, -XC3CC and -XC3DD with trunnion bracket.

Refer to pages 38 to 45 for cylinders with auto switches.

- Auto switch proper mounting position (detection at stroke end) and its mounting height
- Minimum stroke for auto switch mounting
- Auto switch mounting brackets/Part no.
- Operating range

## Specifications

Bore size [mm]	32	40	50	63	80	100
<b>Action</b>	Double acting, Single rod					
<b>Fluid</b>	Air					
<b>Proof pressure</b>	1.5 MPa					
<b>Maximum operating pressure</b>	1.0 MPa					
<b>Minimum operating pressure</b>	0.05 MPa					
<b>Ambient and fluid temperature</b>	Without auto switch: -10 to 70°C With auto switch: -10 to 60°C (No freezing)					
<b>Lubricant</b>	Non-lube					
<b>Piston speed</b>	50 to 1000 mm/s					
<b>Stroke length tolerance</b>	Up to 250: $^{+1.0}_0$ , 251 to 1000: $^{+1.4}_0$ , 1001 to 1500: $^{+1.8}_0$					
<b>Cushion</b> <small>Note)</small>	Air cushion or Rubber bumper					
<b>Port size (Rc, NPT, G)</b>	1/8	1/4	3/8	1/2		
<b>Mounting</b>	Basic, Axial foot, Rod flange, Head flange, Single clevis, Double clevis, Center trunnion					
<b>Non-rotating accuracy</b>	$\pm 0.5^\circ$		$\pm 0.5^\circ$		$\pm 0.3^\circ$	
<b>Allowable rotating torque N·m or less</b>	0.25	0.45	0.64	0.79	0.93	

Note) Kinetic energy absorbable by the cushion mechanism is identical to double acting single rod.

## Standard Strokes

Bore size	Standard stroke [mm]
<b>32</b>	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500
<b>40</b>	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500
<b>50</b>	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600
<b>63</b>	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600
<b>80</b>	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600, 700
<b>100</b>	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600, 700

Manufacture of intermediate strokes is possible. (Spacers are not used.)

## Accessories

Mounting		Basic	Axial foot	Rod flange	Head flange	Single clevis	Double clevis	Center trunnion
Standard	Rod end nut	●	●	●	●	●	●	●
	Clevis pin	—	—	—	—	—	●	—
Option	Single knuckle joint	●	●	●	●	●	●	●
	Double knuckle joint (with pin)	●	●	●	●	●	●	●
	Rod boot	●	●	●	●	●	●	●

\* Refer to page 14 for dimensions and part numbers. (Except rod boot)

## Rod Boot Material

Symbol	Material	Max. ambient temp.
<b>J</b>	Nylon tarpaulin	70°C
<b>K</b>	Heat resistant tarpaulin	110°C*

\* Max. ambient temperature for rod boot itself.

## Mounting Brackets/Part No.

Bore size [mm]	32	40	50	63	80	100
Axial foot <sup>Note 1)</sup>	MB-L03	MB-L04	MB-L05	MB-L06	MB-L08	MB-L10
Rod/Head flange	MB-F03	MB-F04	MB-F05	MB-F06	MB-F08	MB-F10
Single clevis	MB-C03	MB-C04	MB-C05	MB-C06	MB-C08	MB-C10
Double clevis	MB-D03	MB-D04	MB-D05	MB-D06	MB-D08	MB-D10

Note 1) Order two foots per cylinder.

Note 2) Accessories for each mounting bracket are as follows. Axial foot, Rod/Head flange, Single clevis/Body mounting bolt; Double clevis/Body mounting bolt, Clevis pin, Flat washers and Split pins. → Refer to page 14 for details.

## Theoretical Force

OUT side is identical to double acting single rod. Refer to the table below for IN side.

Bore size [mm]	Piston area [mm <sup>2</sup> ]
32	675
40	1082
50	1651
63	2804
80	4568
100	7223

Theoretical force [N] = Pressure [MPa] x Piston area [mm<sup>2</sup>]

## Weights

Bore size [mm]		32	40	50	63	80	100
Basic weight	Basic	0.47	0.64	1.11	1.35	2.54	3.52
	Axial foot	0.59	0.78	1.33	1.63	3.04	4.19
	Rod/Head flange	0.76	1.01	1.56	2.14	3.99	6.84
	Single clevis	0.72	0.87	1.45	1.98	3.65	6.70
	Double clevis	0.73	0.91	1.54	2.14	3.94	7.22
	Center trunnion	0.76	1.00	1.59	2.15	4.09	7.20
Additional weight per 50 mm of stroke	All mounting brackets	0.12	0.15	0.24	0.26	0.39	0.50
Accessories	Single knuckle joint	0.15	0.23	0.26	0.26	0.60	0.83
	Double knuckle joint (with pin)	0.22	0.37	0.43	0.43	0.87	1.27


Calculation

Example) **MBKB32-100Z** (Basic, ø32, 100 stroke)

- Basic weight..... 0.47 (Basic, ø32)
- Additional weight..... 0.12/50 stroke
- Cylinder stroke..... 100 stroke

$$0.47 + 0.12 \times 100/50 = \mathbf{0.71 \text{ kg}}$$

## Construction



## Component Parts

No.	Description	Material	Q'ty	Note
1	Rod cover	Aluminum die-casted	1	Trivalent chromated
2	Head cover	Aluminum die-casted	1	Trivalent chromated
3	Cylinder tube	Aluminum alloy	1	Hard anodized
4	Piston rod	Stainless steel	1	
5	Piston	Aluminum alloy	1	
6	Cushion ring	Rolled steel	2	Zinc chromated
7	Piston nut	Rolled steel	1	Zinc chromated
8	Non-rotating guide	Bearing alloy	1	
9	Cushion valve	Steel wire	2	Trivalent zinc chromated
10	Retaining ring	Spring steel	2	ø40 to ø100
11	Tie-rod	Carbon steel	4	Trivalent zinc chromated

No.	Description	Material	Q'ty	Note
12	Tie-rod nut	Carbon steel	8	Trivalent zinc chromated
13	Wear ring	Resin	1	
14*	Rod seal	NBR	1	
15*	Piston seal	NBR	1	
16*	Cushion seal	Urethane	2	
17	Cushion valve seal	NBR	2	
18*	Cylinder tube gasket	NBR	2	
19	Rod end nut	Rolled steel	1	Trivalent zinc chromated
20	Magnet	—	(1)	
21	Hexagon socket head set screw	Steel wire	2	Trivalent black zinc chromated

## Replacement Parts/Seal Kit


Bore size [mm]	Kit no.	Contents
32	MBK32Z-PS	Set of the nos. 14, 15, 16, 18
40	MBK40Z-PS	
50	MBK50Z-PS	
63	MBK63Z-PS	
80	MBK80Z-PS	
100	MBK100Z-PS	

\* Seal kits consist of items 14, 15, 16, 18, and can be ordered by using the seal kit number corresponding to each bore size.  
 \* Seal kit includes a grease pack (ø32 to 50: 10 g, ø63, 80: 20 g, ø100: 30 g).  
 Order with the following part number when only the grease pack is needed.  
**Grease pack part number: GR-S-010 (10 g), GR-S-020 (20 g)**

\* Model without air cushion is designed to include rubber bumpers. The overall length is longer than the cylinder with air cushion as follows because the bumpers are attached to the both sides of the piston;  
 ø32, ø40: +6 mm, ø50, ø63: +8 mm, ø80, ø100: +10 mm

## Without Mounting Bracket

### Basic: (B)



Bore size [mm]	A	AL	B	B <sub>1</sub>	C	D	E	F	G	H	H <sub>1</sub>	J	MA	MB	MM	N	P	S	V	W	ZZ
32	22	19.5	46	17	32.5	12.2	30	13	13	47	6	M6 x 1	16	4	M10 x 1.25	27	1/8	84	4	6.5	135
40	30	27	52	22	38	14.2	35	13	14	51	8	M6 x 1	16	4	M14 x 1.5	27	1/4	84	4	9	139
50	35	32	65	27	46.5	19	40	14	15.5	58	11	M8 x 1.25	16	5	M18 x 1.5	31.5	1/4	94	5	10.5	156
63	35	32	75	27	56.5	19	45	14	16.5	58	11	M8 x 1.25	16	5	M18 x 1.5	31.5	3/8	94	9	12	156
80	40	37	95	32	72	23	45	20	19	72	13	M10 x 1.5	16	5	M22 x 1.5	38	3/8	114	11.5	14	190
100	40	37	114	41	89	27	55	20	19	72	16	M10 x 1.5	16	5	M26 x 1.5	38	1/2	114	17	15	190

The dimensions for each mounting style and the dimensions with rod boot are the same as those for standard model (double acting, single rod).

# Air Cylinder: Non-rotating Rod Type Double Acting, Double Rod Series **MBKW** ø32, ø40, ø50, ø63, ø80, ø100

RoHS

## How to Order



**MBKW** **L** **32** **-150** **Z-**

**With auto switch** **MDBKW** **L** **32** **-150** **Z-M9BW**

**With auto switch**  
(Built-in magnet)

**Mounting style**

<b>B</b>	Basic/Without bracket
<b>L</b>	Axial foot
<b>F</b>	Rod flange
<b>T</b>	Center trunnion

\* Mounting brackets other than trunnion type are shipped together.

**Bore size**

<b>32</b>	32 mm
<b>40</b>	40 mm
<b>50</b>	50 mm
<b>63</b>	63 mm
<b>80</b>	80 mm
<b>100</b>	100 mm

**Port thread type**

<b>Nil</b>	Rc
<b>TN</b>	NPT
<b>TF</b>	G

**Cylinder stroke [mm]**  
Refer to "Standard Strokes" on page 26.

**Auto switch**

<b>Nil</b>	Without auto switch
------------	---------------------

\* For applicable auto switches, refer to the table below.

**Number of auto switches**

<b>Nil</b>	2 pcs.
<b>S</b>	1 pc.
<b>3</b>	3 pcs.
<b>n</b>	"n" pcs.

**Made to Order**  
For details, refer to page 26.

**Suffix (Cushion)**

<b>Nil</b>	Air cushion
<b>N*</b>	Rubber bumper

\* Since the bumpers are attached to the both sides of the piston for rubber bumper type, the overall length is longer than the cylinder with air cushion as follows: ø32, ø40: +6 mm, ø50, ø63: +8 mm, ø80, ø100: +10 mm.

**Suffix (Rod boot)**

<b>Nil</b>	None
<b>J</b>	Nylon tarpaulin (one end)
<b>JJ</b>	Nylon tarpaulin (both ends)
<b>K</b>	Heat resistant tarpaulin (one end)
<b>KK</b>	Heat resistant tarpaulin (both ends)

**Applicable Auto Switches**/Refer to the **WEB catalog** or the Best Pneumatics No. 2 for further information on auto switches.

Type	Special function	Electrical entry	Indicator light	Wiring (Output)	Load voltage		Auto switch model		Lead wire length [m]				Pre-wired connector	Applicable load				
					DC		AC	Tie-rod mounting	Band mounting	0.5 (Nil)	1 (M)	3 (L)		5 (Z)				
Solid state auto switch	—	Grommet	Yes	3-wire (NPN)	24 V	5 V, 12 V	—	M9N	—	●	●	●	○	○	IC circuit	Relay, PLC		
				3-wire (PNP)				M9P	—	●	●	●	○	○				
		2-wire		M9B				—	●	●	●	○	○					
		Terminal conduit		3-wire (NPN)	24 V	5 V, 12 V	—	—	G39	—	—	—	—	—				
	2-wire			—				K39	—	—	—	—						
	Diagnostic indication (2-color indication)	Grommet		3-wire (NPN)				24 V	5 V, 12 V	—	M9NW	—	●	●	●		○	○
				3-wire (PNP)	M9PW	—	●				●	●	○	○				
				2-wire	M9BW	—	●				●	●	○	○	—			
				3-wire (NPN)	M9NA*1	—	○	○	●		○	○	IC circuit					
	3-wire (PNP)			M9PA*1	—	○	○	●	○		○							
	2-wire			M9BA*1	—	○	○	●	○		○	—						
	Diagnostic output (2-color indication)			4-wire (NPN)	5 V, 12 V	F59F	—	●	—		●		○	○	IC circuit			
				Magnetic field resistant (2-color indication)	2-wire (Non-polar)	—	P3DWA***	—	●		—	●	●	○			—	
							P3DW***	—	●		—	●	●	○				
P4DW			—				—	—	●		●	○						
Reed auto switch	—	Grommet	Yes				3-wire (Equiv. to NPN)	24 V	12 V	—	A96	—	●	—	●	—	—	IC circuit
				No	2-wire	100 V	A93				—	●	●	●	●	—	—	
						100 V or less	A90				—	●	—	●	—	IC circuit		
						100 V, 200 V	A54				—	●	—	●	●			—
		200 V or less				A64	—				●	—	●	—	—			
		Terminal conduit		—		—	A33				—	—	—	—			—	
				DIN terminal		100 V, 200 V	—				A34	—	—	—		—		
		Grommet				—	—				A44	—	—	—		—	—	
	Diagnostic indication (2-color indication)			—		—	A59W				—	●	—	●	—	—		—

\*1 Water resistant type auto switches can be mounted on the above models, but in such case SMC cannot guarantee water resistance.

Please contact SMC regarding water resistant types with the above model numbers.

\* Lead wire length symbols: 0.5 m ..... Nil (Example) M9NW 3 m ..... L (Example) M9NWL  
1 m ..... M (Example) M9NWM 5 m ..... Z (Example) M9NWX

\* Solid state auto switches marked with "○" are produced upon receipt of order.

\* Since there are other applicable auto switches than listed above, refer to page 45 for details.

\* For details about auto switches with pre-wired connector, refer to the **WEB catalog** or the Best Pneumatics No. 2.

For the D-P3DWA□, refer to the **WEB catalog**.


\* The D-A9□/M9□□□/P3DWA□ auto switches are shipped together, (but not assembled). (However, auto switch mounting brackets are assembled for the D-A9□/M9□□□ before shipment.)

\*\*\* The D-P3DWA cannot be mounted on ø32. Use the D-P3DW.




# Air Cylinder: Non-rotating Rod Type Double Acting, Double Rod **Series MBKW**

## Specifications



**Symbol**  
Double acting



**Made to Order**  
(For details, refer to pages 47 to 63.)

Symbol	Specifications
<b>-XC3</b>	Special port location*
<b>-XC6</b>	Made of stainless steel
<b>-XC7</b>	Tie-rod, cushion valve, tie-rod nut, etc. made of stainless steel
<b>-XC30</b>	Rod trunnion

\* The cover shape is the same as the current product.

For special port location (-XC3), the mounting bracket and port location can be determined using the standard product corresponding to the operating conditions. Also, this is only applicable to -XC3BB, -XC3CC and -XC3DD with trunnion bracket.

Bore size [mm]	32	40	50	63	80	100
<b>Action</b>	Double acting, Double rod					
<b>Fluid</b>	Air					
<b>Proof pressure</b>	1.5 MPa					
<b>Max. operating pressure</b>	1.0 MPa					
<b>Min. operating pressure</b>	0.05 MPa					
<b>Ambient and fluid temperature</b>	Without auto switch: -10 to 70°C With auto switch: -10 to 60°C (No freezing)					
<b>Lubrication</b>	Non-lube					
<b>Operating piston speed</b>	50 to 1000 mm/s					
<b>Allowable stroke tolerance</b>	Up to 250: $^{+1.0}_0$ , 251 to 800: $^{+1.4}_0$					
<b>Cushion</b> <small>Note)</small>	Air cushion or Rubber bumper					
<b>Port size (Rc, NPT, G)</b>	1/8	1/4	3/8	1/2		
<b>Mounting</b>	Basic, Axial foot, Rod flange, Center trunnion					
<b>Non-rotating accuracy</b>	$\pm 0.5^\circ$		$\pm 0.5^\circ$		$\pm 0.3^\circ$	
<b>Allowable rotating torque N·m or less</b>	0.25	0.45	0.64	0.79	0.93	

Note) Kinetic energy absorbable by cushion mechanism is identical to double acting single rod.

## Standard Strokes

Bore size	Standard stroke [mm]
<b>32</b>	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500
<b>40</b>	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500
<b>50</b>	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600
<b>63</b>	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600
<b>80</b>	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600, 700
<b>100</b>	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600, 700

Manufacture of intermediate strokes is possible. (Spacers are not used.)

## Accessories

Mounting		Basic	Axial foot	Rod flange	Center trunnion
Standard	Rod end nut	●	●	●	●
	Single knuckle joint	●	●	●	●
Option	Double knuckle joint (with pin)	●	●	●	●
	Rod boot	●	●	●	●

\* Refer to page 14 for dimensions and part numbers. (Except rod boot)

## Rod Boot Material

Symbol	Material	Max. ambient temp.
<b>J</b>	Nylon tarpaulin	70°C
<b>K</b>	Heat resistant tarpaulin	110°C*

\* Max. ambient temperature for rod boot itself.

## Mounting Brackets/Part No.

Bore size [mm]	32	40	50	63	80	100
Axial foot	MB-L03	MB-L04	MB-L05	MB-L06	MB-L08	MB-L10
Rod flange	MB-F03	MB-F04	MB-F05	MB-F06	MB-F08	MB-F10

Note) Order two foots per cylinder.

# Series MBKW

## Theoretical Force

(Unit: N) OUT ← IN →

Bore size [mm]	Rod dia. [mm]	Operating direction	Piston area [mm <sup>2</sup> ]	Operating pressure [MPa]								
	Width across flats [mm]			0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
32	12	OUT	691	138	207	276	346	415	484	553	622	691
	12.2	IN	675	135	203	270	338	405	473	540	608	675
40	16	OUT	1056	211	317	422	528	634	739	845	950	1056
	14.2	IN	1082	216	325	433	541	649	757	866	974	1082
50	20	OUT	1649	330	495	660	825	989	1154	1319	1484	1649
	19	IN	1651	330	495	660	826	991	1156	1321	1486	1651
63	20	OUT	2803	561	841	1121	1402	1682	1962	2242	2523	2803
	19	IN	2804	561	841	1122	1402	1682	1963	2243	2524	2804
80	25	OUT	4536	907	1361	1814	2268	2722	3175	3629	4082	4536
	23	IN	4568	914	1370	1827	2284	2741	3198	3654	4111	4568
100	30	OUT	7147	1429	2144	2859	3574	4288	5003	5718	6432	7147
	27	IN	7223	1445	2167	2889	3612	4334	5056	5778	6501	7223

Note) Theoretical force [N] = Pressure [MPa] x Piston area [mm<sup>2</sup>]

## Weights/Aluminum Tube

Bore size [mm]		32	40	50	63	80	100
Basic weight	Basic	0.56	0.77	1.34	1.60	2.99	4.10
	Axial foot	0.68	0.91	1.56	1.88	3.49	4.76
	Rod flange	0.85	1.14	1.79	2.39	4.44	7.41
	Center trunnion	0.85	1.13	1.82	2.40	4.54	7.77
Additional weight per 50 mm of stroke	All mounting brackets	0.16	0.23	0.37	0.38	0.60	0.79
Accessories	Single knuckle joint	0.15	0.23	0.26	0.26	0.6	0.83
	Double knuckle joint (with pin)	0.22	0.37	0.43	0.43	0.87	1.27

[kg]


Calculation

Example) **MBKW32-100Z** (Basic, ø32, 100 st)

- Basic weight ...0.56 (Basic, ø32)
- Additional weight ...0.16/50 stroke

$$0.56 + 0.16 \times 100/50 = \mathbf{0.88 \text{ kg}}$$

## Construction



### Component Parts

No.	Description	Material	Q'ty	Note
1-1	Rod cover	Aluminum die-casted	1	Non-rotating rod
1-2	Rod cover	Aluminum die-casted	1	Standard
2	Cylinder tube	Aluminum alloy	1	Hard anodized
3	Piston rod A	Stainless steel	1	Non-rotating rod
4	Piston rod B	Carbon steel	1	Standard
5	Piston	Aluminum alloy	1	
6	Cushion ring	Rolled steel	2	Zinc chromated
7-1	Non-rotating guide	Bearing alloy	1	Non-rotating rod
7-2	Bushing	Bearing alloy	1	Standard
8	Cushion valve	Steel wire	2	Trivalent zinc chromated
9	Retaining ring	Spring steel	2	ø40 to ø100
10	Tie-rod	Carbon steel	4	Trivalent zinc chromated
11	Tie-rod nut	Carbon steel	8	Trivalent zinc chromated
12-1*	Rod seal	NBR	1	Non-rotating rod
12-2*	Rod seal	NBR	1	Standard
13*	Piston seal	NBR	1	
14*	Cushion seal	Urethane	2	
15	Cushion valve seal	NBR	2	
16*	Cylinder tube gasket	NBR	2	

No.	Description	Material	Q'ty	Note
17	Rod end nut	Rolled steel	2	Trivalent zinc chromated
18	Magnet	—	(1)	
19	Hexagon socket head set screw	Steel wire	2	Trivalent black zinc chromated

### Replacement Parts/Seal Kit

Bore size [mm]	Kit no.	Contents
32	MBKW32Z-PS	Set of the nos. 12, 13, 14, 16
40	MBKW40Z-PS	
50	MBKW50Z-PS	
63	MBKW63Z-PS	
80	MBKW80Z-PS	
100	MBKW100Z-PS	

\* Seal kits consist of items 12, 13, 14, 16, and can be ordered by using the seal kit number corresponding to each bore size.

\* Trunnion type should not be disassembled. (Refer to page 64.)


\* Seal kit includes a grease pack (ø32 to 50: 10 g, ø63, 80: 20 g, ø100: 30 g).

Order with the following part number when only the grease pack is needed.


**Grease pack part number: GR-S-010 (10 g), GR-S-020 (20 g)**

## Standard

### Basic: (B)



### Positional relationship between port and cushion valve



Bore size [mm]	A	AL	B	B <sub>1</sub>	C	D	E	F	G	H	H <sub>1</sub>	J	K	KA	KB
32	22	19.5	46	17	32.5	12	30	13	13	47	6	M6 x 1	6	12.2	10
40	30	27	52	22	38	16	35	13	14	51	8	M6 x 1	6	14.2	14
50	35	32	65	27	46.5	20	40	14	15.5	58	11	M8 x 1.25	7	19	18
63	35	32	75	27	56.5	20	45	14	16.5	58	11	M8 x 1.25	7	19	18
80	40	37	95	32	72	25	45	20	19	72	13	M10 x 1.5	10	23	22
100	40	37	114	41	89	30	55	20	19	72	16	M10 x 1.5	10	27	26

Bore size [mm]	MA	MB	MM	N	P	S*	V	W	ZZ*
32	16	4	M10 x 1.25	27	1/8	84	4	6.5	178
40	16	4	M14 x 1.5	27	1/4	84	4	9	186
50	16	5	M18 x 1.5	31.5	1/4	94	5	10.5	210
63	16	5	M18 x 1.5	31.5	3/8	94	9	12	210
80	16	5	M22 x 1.5	38	3/8	114	11.5	14	258
100	16	5	M26 x 1.5	38	1/2	114	17	15	258

\* Model without air cushion is designed to include rubber bumpers. The overall length is longer than the cylinder with air cushion as follows because the bumpers are attached to the both sides of the piston; ø32, ø40: +6 mm, ø50, ø63: +8 mm, ø80, ø100: +10 mm

The dimensions for each mounting style are the same as those for standard model (double acting, double rod). Refer to pages 19 and 20.

# Air Cylinder: With End Lock

## Series *MBB*

ø32, ø40, ø50, ø63, ø80, ø100

RoHS

### How to Order



**MBB L 32 - 50 - H N -**

**With auto switch** **MDBB L 32 - 50 - H N - M9BW -**

**Mounting style**

<b>B</b>	Basic/Without bracket
<b>L</b>	Axial foot
<b>F</b>	Rod flange
<b>G</b>	Head flange
<b>C</b>	Single clevis
<b>D</b>	Double clevis
<b>T</b>	Center trunnion

**Bore size**

<b>32</b>	32 mm
<b>40</b>	40 mm
<b>50</b>	50 mm
<b>63</b>	63 mm
<b>80</b>	80 mm
<b>100</b>	100 mm

**Port thread type**

<b>Nil</b>	Rc
<b>TN</b>	NPT
<b>TF</b>	G

**Cylinder stroke [mm]**

Refer to "Standard Strokes" on page 30.

**Manual release**

<b>N</b>	Non-locking
<b>L</b>	Locking

**Locking position**

<b>H</b>	Locking at head end
<b>R</b>	Locking at rod end
<b>W</b>	Locking at both ends

**Suffix (Rod boot)**

<b>Nil</b>	None
<b>J</b>	Nylon tarpaulin
<b>K</b>	Heat resistant tarpaulin

**Number of auto switches**

<b>Nil</b>	2 pcs.
<b>S</b>	1 pc.
<b>3</b>	3 pcs.
<b>n</b>	"n" pcs.

**Auto switch**

<b>Nil</b>	Without auto switch
------------	---------------------

\* For applicable auto switches, refer to the table below.

#### Built-in Magnet Cylinder Model

If a built-in magnet cylinder without an auto switch is required, there is no need to enter the symbol for the auto switch. (Example) MDBBB40-100

**Applicable Auto Switches**/Refer to the **WEB catalog** or the Best Pneumatics No. 2 for further information on auto switches.

Type	Special function	Electrical entry	Indicator light	Wiring (Output)	Load voltage		Auto switch model		Lead wire length [m]				Pre-wired connector	Applicable load						
					DC		AC	Tie-rod mounting	Band mounting	0.5 (Nil)	1 (M)	3 (L)				5 (Z)				
Solid state auto switch	—	Grommet	Yes	3-wire (NPN)	24 V	5 V, 12 V	—	M9N	—	●	●	●	○	○	IC circuit	Relay, PLC				
				3-wire (PNP)				M9P	—	●	●	●	○	○						
		2-wire		M9B				—	●	●	●	○	○	—						
		Terminal conduit		3-wire (NPN)	24 V	5 V, 12 V	—	G39	—	—	—	—	—							
	2-wire			—				K39	—	—	—	—								
	Diagnostic indication (2-color indication)	Grommet		3-wire (NPN)				5 V, 12 V	M9NW	—	●	●	●	○	○		IC circuit			
				3-wire (PNP)	M9PW	—	●		●	●	○	○								
				2-wire	M9BW	—	●		●	●	○	○	—							
				Water resistant (2-color indication)	3-wire (NPN)	24 V	5 V, 12 V	M9NA*1	—	○	○	●		○	○		IC circuit			
	3-wire (PNP)				M9PA*1			—	○	○	●	○	○							
	2-wire				M9BA*1			—	○	○	●	○	○	—						
	Diagnostic output (2-color indication)				Grommet	4-wire (NPN)	5 V, 12 V	F59F	—	●	—	●	○		○		IC circuit			
			Magnetic field resistant (2-color indication)	—		P3DWA***	—	●	—	●	●	○	—							
		P3DW***				—	●	—	●	●	○									
P4DW		—				—	—	●	●	○										
Reed auto switch	—	Grommet				Yes	3-wire (Equiv. to NPN)	—	5 V	—	A96	—	●	—	●	—	—	IC circuit	—	
			2-wire	24 V			12 V				100 V	A93	—	●	●	●	●	—		—
											100 V or less	A90	—	●	—	●	—	—		
											100 V, 200 V	A54	—	●	—	●	●	—		
		200 V or less			A64			—	●	—	●	—	—							
		Terminal conduit	—	—	A33		—	—	—	—	—	—								
			100 V, 200 V	—	A34		—	—	—	—	—									
		DIN terminal	Grommet	—	—		A44	—	—	—	—		—	—						
	Diagnostic indication (2-color indication)			—	—		A59W	—	●	—	●		—		—					

\*1 Water resistant type auto switches can be mounted on the above models, but in such case SMC cannot guarantee water resistance.

Please contact SMC regarding water resistant types with the above model numbers.

\* Lead wire length symbols: 0.5 m ..... Nil (Example) M9NW 3 m ..... L (Example) M9NWL  
1 m ..... M (Example) M9NWM 5 m ..... Z (Example) M9NWZ

\* Solid state auto switches marked with "○" are produced upon receipt of order.


\* Since there are other applicable auto switches than listed above, refer to page 45 for details.

\* For details about auto switches with pre-wired connector, refer to the **WEB catalog** or the Best Pneumatics No. 2.


For the D-P3DWA□, refer to the **WEB catalog**.

\* The D-A9□/M9□□□/P3DWA□A auto switches are shipped together, (but not assembled). (However, auto switch mounting brackets are assembled for the D-A9□/M9□□□ before shipment.)

\*\*\* The D-P3DWA cannot be mounted on ø32. Use the D-P3DW.



**Symbol**  
Air cushion



**Made to Order**  
(For details, refer to pages 47 to 63.)

Symbol	Specifications
-XA□	Change of rod end shape
-XC7	Tie-rod, cushion valve, tie-rod nut, etc. made of stainless steel
-XC10	Dual stroke cylinder/Double rod type
-XC14	Change of trunnion bracket mounting position
-XC27	Double clevis and double knuckle joint pins made of stainless steel
-XC29	Double knuckle joint with spring pin
-XC30	Rod trunnion

\* All Made-to-Order products have the same cover shapes as the current products.

Refer to pages 38 to 45 for cylinders with auto switches.

- Auto switch proper mounting position (detection at stroke end) and its mounting height
- Minimum stroke for auto switch mounting
- Auto switch mounting brackets/Part no.
- Operating range

## Specifications

Bore size [mm]	32	40	50	63	80	100
<b>Action</b>	Double acting, Single rod					
<b>Fluid</b>	Air					
<b>Proof pressure</b>	1.5 MPa					
<b>Max. operating pressure</b>	1.0 MPa					
<b>Min. operating pressure</b>	0.15 MPa*					
<b>Ambient and fluid temperature</b>	Without auto switch: -10 to 70°C With auto switch: -10 to 60°C (No freezing)					
<b>Lubrication</b>	Non-lube					
<b>Operating piston speed</b>	50 to 1000 mm/s					
<b>Allowable stroke tolerance</b>	Up to 250: $^{+1.0}_0$ , 251 to 1000: $^{+1.4}_0$ , 1001 to 1500: $^{+1.8}_0$					
<b>Cushion</b>	Air cushion					
<b>Port size (Rc, NPT, G)</b>	1/8	1/4	3/8	1/2		
<b>Mounting</b>	Basic, Axial foot, Rod flange, Head flange, Single clevis, Double clevis, Center trunnion					

\* 0.05 MPa except locking parts

## Locking Specifications

Locking position	Head end, Rod end, Both ends					
	ø32	ø40	ø50	ø63	ø80	ø100
Holding force (Max.) N	550	860	1340	2140	3450	5390
Back lash	1.5 mm or less					
Manual release	Non-locking type, Locking type					

## Standard Strokes

Bore size	Standard stroke [mm]
<b>32</b>	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500
<b>40</b>	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500
<b>50</b>	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600
<b>63</b>	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600
<b>80</b>	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600, 700, 800
<b>100</b>	25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 350, 400, 450, 500, 600, 700, 800

Intermediate strokes are available. (No spacer is used.)

## Accessories

Mounting		Basic	Axial foot	Rod flange	Head flange	Single clevis	Double clevis	Center trunnion
Standard	Rod end nut	●	●	●	●	●	●	●
	Clevis pin	—	—	—	—	—	●	—
	Locking release bolt (N type only)	●	●	●	●	●	●	●
Option	Single knuckle joint	●	●	●	●	●	●	●
	Double knuckle joint (with pin)	●	●	●	●	●	●	●
	Rod boot	●	●	●	●	●	●	●

\* Refer to page 14 for dimensions and part numbers. (Except locking release bolt and rod boot)



# Series MBB

## Weights/Aluminum Tube

Bore size [mm]		32	40	50	63	80	100
Basic weight	Basic	0.50	0.69	1.19	1.47	2.73	3.7
	Axial foot	0.68	0.93	1.56	1.93	3.61	4.8
	Rod/Head flange	0.79	1.06	1.64	2.26	4.18	7.01
	Single clevis	0.75	0.92	1.53	2.1	3.84	6.87
	Double clevis	0.76	0.96	1.62	2.26	4.13	7.39
	Center trunnion	0.79	1.05	1.67	2.27	4.28	7.37
Additional weight per 50 mm of stroke	All mounting brackets	0.11	0.16	0.26	0.27	0.42	0.56
Accessories	Single knuckle joint	0.15	0.23	0.26	0.26	0.60	0.83
	Double knuckle joint (with pin)	0.22	0.37	0.43	0.43	0.87	1.27

## Mounting Brackets/Part No.

Bore size [mm]	32	40	50	63	80	100
Axial foot <small>Note 1)</small>	MB-L03	MB-L04	MB-L05	MB-L06	MB-L08	MB-L10
Rod/Head flange	MB-F03	MB-F04	MB-F05	MB-F06	MB-F08	MB-F10
Single clevis	MB-C03	MB-C04	MB-C05	MB-C06	MB-C08	MB-C10
Double clevis	MB-D03	MB-D04	MB-D05	MB-D06	MB-D08	MB-D10

Note 1) Order two foots per cylinder.

Note 2) Accessories for each mounting bracket are as follows.

Axial foot, Rod/Head flange, Single clevis/Body mounting bolt; Double clevis/Body mounting bolt, Clevis pins, Flat washer and Split pins. → Refer to page 14 for details.

## Additional Weight of Locking Part

Bore size [mm]		32	40	50	63	80	100
Manual release non-locking (N)	Locking at head end (H)	0.08	0.13	0.21	0.30	0.75	1.1
	Locking at rod end (R)	0.08	0.13	0.20	0.29	0.71	1.03
	Locking at both ends (W)	0.16	0.26	0.41	0.59	1.46	2.13
Manual release locking (L)	Locking at head end (H)	0.09	0.15	0.23	0.32	0.78	1.13
	Locking at rod end (R)	0.09	0.15	0.22	0.31	0.74	1.06
	Locking at both ends (W)	0.18	0.30	0.45	0.63	1.52	2.19

Calculation

Example) **MBBL32-100-HN**




- Basic weight..... 0.68
- Additional weight..... 0.11/50 stroke
- Cylinder stroke..... 100 stroke
- Locking weight ..... 0.08 (Locking at head end, manual release non-locking type)

$$0.68 + 0.11 \times 100/50 + 0.08 = \mathbf{0.98 \text{ kg}}$$



## Construction

### Locking at head end

Manual release non-locking type: N



### Locking at rod end



Manual release locking type: L

### Component Parts

No.	Description	Material	Note
1	Rod cover	Aluminum alloy	Metallic painted
2	Head cover	Aluminum alloy	Metallic painted
3	Cylinder tube	Aluminum alloy	Hard anodized
4	Piston rod	Carbon steel	Hard chrome plating
5	Piston	Aluminum alloy	Chromated
6	Cushion ring	Aluminum alloy	Anodized
7	Bushing	Bearing alloy	
8	Cushion valve	Steel wire	Trivalent zinc chromated
9	Retaining ring	Steel for spring	ø40 to ø100
10	Tie-rod	Carbon steel	Trivalent zinc chromated
11	Tie-rod nut	Carbon steel	Trivalent zinc chromated
12	Wear ring	Resin	
13	Rod end nut	Carbon steel	Trivalent zinc chromated
14A	Cover A	Aluminum alloy	Painted black
14B	Cover B	Carbon steel	Tufftride
15	Rubber cover	Synthetic rubber	
16	Piston holder	Urethane	

### Replacement Parts/Seal Kit (Locking at head or rod end)

Bore size [mm]	Kit no.	Contents
32	MBB32-PS	Set of the nos. 29, 30, 31, 32, 33
40	MBB40-PS	
50	MBB50-PS	
63	MBB63-PS	
80	MBB80-PS	
100	MBB100-PS	

\* Seal kits consist of items 29 to 33, and can be ordered by using the seal kit number corresponding to each bore size.  
 \* Trunnion type should not be disassembled. (Refer to page 64.)  
 \* Seal kit includes a grease pack (ø32 to 50: 10 g, ø63, 80: 20 g, ø100: 30 g).  
 Order with the following part number when only the grease pack is needed.  
**Grease pack part number: GR-S-010 (10 g), GR-S-020 (20 g)**

### Component Parts

No.	Description	Material	Note
17	Lock spring	Steel wire	
18	Bumper	Urethane	
19	Lock piston	Carbon steel	Hardened, Hard chrome plating
20	Lock bushing	Copper alloy	
21	Bolt with hex. hole	Alloyed steel	Black zinc chromated
22	M/O knob	Zinc alloy	Painted black
23	M/O bolt	Alloyed steel	Black zinc chromated, Painted red
24	M/O spring	Steel wire	Zinc chromated
25	Stopper ring	Carbon steel	Zinc chromated
26	Seal retainer	Rolled steel	ø80, ø100 only
27	Cushion valve seal	NBR	
28	Piston gasket	NBR	
29*	Cushion seal	Urethane	
30*	Rod seal	NBR	
31*	Piston seal	NBR	
32*	Cylinder tube gasket	NBR	
33*	Lock piston seal	NBR	

### Replacement Parts/Seal Kit (Locking at both ends)

Bore size [mm]	Kit no.	Contents
32	MBB32-PS-W	Set of the nos. 29, 30, 31, 32, 33
40	MBB40-PS-W	
50	MBB50-PS-W	
63	MBB63-PS-W	
80	MBB80-PS-W	
100	MBB100-PS-W	


**Series *MBB***

**Basic: (B)**


**Locking at head end: MBBB** **Bore size** **Port thread type** – **Stroke** – H□

**Manual release non-locking type: N**


**Manual release locking type: L**



**Locking at rod end: MBBB**   –  – R



**Locking at both ends: MBBB**   –  – W



**-H□/-R□**

[mm]



Bore size [mm]	AL	KA	A	B	C	D	DL	E	F	G	GB	H <sub>i</sub>	H	HR	HN	J	K	LL	MA	MB
<b>32</b>	19.5	10	22	46	32.5	12	9	30	13	13	21	6	47	33.5	45	M6 x 1	6	15	16	4
<b>40</b>	27	14	30	52	38	16	12	35	13	14	27	8	51	38.5	52.5	M6 x 1	6	21	16	4
<b>50</b>	32	18	35	65	46.5	20	13	40	14	15.5	27.5	11	58	45	59	M8 x 1.25	7	21	16	5
<b>63</b>	32	18	35	75	56.5	20	13	45	14	16.5	28.5	11	58	50	64	M8 x 1.25	7	21	16	5
<b>80</b>	37	22	40	95	72	25	16	45	20	19	37	13	72	62	76.5	M10 x 1.5	10	30	16	5
<b>100</b>	37	26	40	114	89	30	16	55	20	19	37	16	72	71.5	86	M10 x 1.5	10	30	16	5

**-W** ☐

Bore size [mm]	MM	MO	N	NB	P	RF	S	V	W	WL	ZZ	S	ZZ
<b>32</b>	M10 x 1.25	15	27	35	1/8	11	92	4	6.5	24	143	100	151
<b>40</b>	M14 x 1.5	19	27	40	1/4	11	97	4	9	24	152	110	165
<b>50</b>	M18 x 1.5	19	31.5	43.5	1/4	11	106	5	10.5	24	168	118	180
<b>63</b>	M18 x 1.5	19	31.5	43.5	3/8	11	106	9	12	24	168	118	180
<b>80</b>	M22 x 1.5	23	38	56	3/8	21	132	11.5	14	40	208	150	226
<b>100</b>	M26 x 1.5	23	38	56	1/2	21	132	17	15	40	208	150	226

## With Mounting Bracket

Axial foot: (L) / Locking at head end: (-H□)





-H□/-R□

[mm] -W□

Bore size [mm]	X	Y	LD	LH	LS	LT	LX	LY	LZ	ZZ	LS	ZZ
32	22	9	7	30	136	3.2	32	53	50	170	144	178
40	24	11	9	33	145	3.2	38	59	55	183	158	196
50	27	11	9	40	160	3.2	46	72.5	70	202	172	214
63	27	14	12	45	160	3.6	56	82.5	80	205	172	217
80	30	14	12	55	192	4.5	72	102.5	100	248	210	266
100	32	16	14	65	196	4.5	89	122	120	252	214	270

Rod flange: (F) / Locking at head end: (-H□)





-H□/-R□/-W□

[mm]

Bore size [mm]	FB	FD	FE	FT	FX	FY	FZ	Fd
32	50	7	3	10	64	32	79	25
40	55	9	3	10	72	36	90	31
50	70	9	2	12	90	45	110	38.5
63	80	9	2	12	100	50	120	39.5
80	100	12	4	16	126	63	153	45
100	120	14	4	16	150	75	178	54

Head flange: (G) / Locking at head end: (-H□)



-H□/-R□


[mm] -W□

Bore size [mm]	FB	FD	FT	FX	FY	FZ	ZZ	ZZ
32	50	7	10	64	32	79	149	157
40	55	9	10	72	36	90	158	171
50	70	9	12	90	45	110	176	188
63	80	9	12	100	50	120	176	188
80	100	12	16	126	63	153	220	238
100	120	14	16	150	75	178	220	238

# Series MBB


## With Mounting Bracket

Single clevis: (C) / Locking at head end: (-H□)




-H□/-R□								[mm] -W□	
Bore size [mm]	L	RR	U	CDH10	CX <sup>-0.1 -0.3</sup>	Z	ZZ	Z	ZZ
32	23	10.5	13	10	14	162	172.5	170	180.5
40	23	11	13	10	14	171	182	184	195
50	30	15	17	14	20	194	209	206	221
63	30	15	17	14	20	194	209	206	221
80	42	23	26	22	30	246	269	264	287
100	42	23	26	22	30	246	269	264	287

Double clevis: (D) / Locking at head end: (-H□)



-H□/-R□								[mm]	-W□	
Bore size [mm]	L	RR	U	CD <sub>H10</sub>	CX <sup>+0.3 +0.1</sup>	CZ	Z	ZZ	Z	ZZ
32	23	10.5	13	10	14	28	162	172.5	170	180.5
40	23	11	13	10	14	28	171	182	184	195
50	30	15	17	14	20	40	194	209	206	221
63	30	15	17	14	20	40	194	209	206	221
80	42	23	26	22	30	60	246	269	264	287
100	42	23	26	22	30	60	246	269	264	287

Center trunnion: (T) / Locking at head end: (-H□)



-H□							[mm] -R□/-W□	
Bore size [mm]	TD e8	TT	TX	TY	TZ	Z	Z	
32	12	17	50	49	74	89	97	
40	16	22	63	58	95	93	106	
50	16	22	75	71	107	105	117	
63	20	28	90	87	130	105	117	
80	20	34	110	110	150	129	147	
100	25	40	132	136	182	129	147	




## Cautions for Using

### 1. Use recommended pneumatic circuit.

#### ⚠ Caution

For correct operation of locking or releasing mechanism, use the following pneumatic circuit.



#### ① Do not use a 3-position solenoid valve.

Avoid using circuit with 3-position solenoid valve (especially closed center, metal seal type).

When pressure is trapped in the port with locking mechanism, end lock is free. When utilizing a 3-position closed center valve, even if the lock is engaged, it may become unlocked due to pressure leakage either across the piston or the valve spool.

#### ② Back pressure is required to release lock.

Before starting operation, supply air to side without locking mechanism as figure above, (or side without locking the piston rod for models with locking at both ends.) Otherwise, lock may not be released. (Refer to "Release of lock".)

#### ③ Release lock when mounting or adjusting the cylinder.

If mounting is done with lock engaged, lock may be damaged.

#### ④ Use with load 50% or less of rated capacity.

If cylinder is used over 50% load capacity, lock may be damaged.

#### ⑤ Do not use multiple cylinders synchronously.

Avoid using 2 or more end lock cylinders synchronously to perform a single task because one of the cylinders may not allow lock to release.

#### ⑥ Use a speed controller as meter-out.

Meter-in control may not allow lock to release.

#### ⑦ Use complete stroke or cylinder at side with lock.

If cylinder piston does not reach end of stroke, lock may not be engaged or released.

### 2. Operating pressure

#### ⚠ Caution

Use pressures 0.15 MPa or more at port with locking mechanism. Otherwise, lock will not be released.

### 3. Exhaust speed

#### ⚠ Caution

When pressures at port with locking mechanism is decreased to 0.05 MPa or less, it is automatically locked. When exhaust pipe at port with locking mechanism is thin and long or speed controller is distanced from cylinder port, exhaust speed is slow and will require additional time for lock engagement. Clogging the silencer mounted on exhaust port of solenoid valve leads to the same result.

### 4. Relationship with cushion

#### ⚠ Caution

When cushion valve at side with locking mechanism is fully closed or nearly fully closed, piston rod may not reach the stroke end. Thus lock is not established. And when locking is done with the cushion valve nearly fully closed, adjust the cushion valve since lock may not be released.

### 5. Release of lock

#### ⚠ Warning

When lock is to be released, supply air pressure to the port without the locking mechanism, this relieves the load from the lock mechanism. (Refer to recommended pneumatic circuit.) When port without lock mechanism is exhausted and locking mechanism is loaded, the lock may be damaged due to excessive force on lock during release. Also, piston rod will operate immediately.

### 6. Manual release


#### ⚠ Caution

##### Non-locking type

Insert attached bolt from upper side of rubber cover (no need to remove rubber cover), tighten locking piston and pull bolt, lock will be released. When bolt is released, locking begins to take place. Thread size, required pulling force and stroke are listed below.

Bore size [mm]	Thread size	Pulling force	Stroke [mm]
32	≥ M2.5 x 0.45 x 25 L	4.9 N	2
40, 50, 63	≥ M3 x 0.5 x 30 L	10 N	3
80, 100	≥ M5 x 0.8 x 40 L	24.5 N	3


\* Remove bolt under normal operations.  
It may cause malfunction of locking and release.



##### Locking type

Turn 90° counterclockwise while pushing the M/O knob. Lock is released when ▲ on the cap and ▼ OFF mark on the M/O knob correspond. (Lock remains released.)

When locking is desired, turn 90° clockwise while fully pushing the M/O knob and correspond ▲ on the cap and ▼ ON mark on the M/O knob. Confirm the correct position by click sound "click". Otherwise, lock may not be engaged.



# Air Cylinder: Low Friction Type

## Series **MB**□**Q**

RoHS

ø32, ø40, ø50, ø63, ø80, ø100

Use the new series “Smooth Cylinder MBY Series” to realize bi-directional low friction and low-speed operation. (Refer to the **WEB catalog** or “CAT. ES20-235” catalog.)

### How to Order

**MB** **L** **Q** **32** **□** - **50** **F** - **□**

**With auto switch** **MDB** **L** **Q** **32** **□** - **50** **F** - **M9BW** **□** - **□**

**With auto switch**  
(Built-in magnet)

**Mounting style**

<b>B</b>	Basic
<b>L</b>	Axial foot
<b>F</b>	Rod flange
<b>G</b>	Head flange
<b>C</b>	Single clevis
<b>D</b>	Double clevis
<b>T</b>	Center trunnion

**Bore size**

<b>32</b>	32 mm
<b>40</b>	40 mm
<b>50</b>	50 mm
<b>63</b>	63 mm
<b>80</b>	80 mm
<b>100</b>	100 mm

**Port thread type**

<b>Nil</b>	Rc
<b>TN</b>	NPT
<b>TF</b>	G

**Direction of low friction**

<b>F</b>	With pressure at head side
<b>B</b>	With pressure at rod side

**Auto switch**

<b>Nil</b>	Without auto switch
------------	---------------------

**Number of auto switches**

<b>Nil</b>	2 pcs.
<b>S</b>	1 pc.
<b>3</b>	3 pcs.
<b>n</b>	“n” pcs.

**Made to Order**

**Built-in Magnet Cylinder Model**  
If a built-in magnet cylinder without an auto switch is required, there is no need to enter the symbol for the auto switch. (Example) MDBBQ40-100

**Cylinder stroke [mm]**


# Series MB

## Auto Switch Mounting


### Auto Switch Proper Mounting Position (Detection at stroke end) and Its Mounting Height

#### <Band mounting>

D-G39/K39/A3□



D-A44



#### <Tie-rod mounting>

D-M9□/M9□V

D-M9□W/M9□WV


D-M9□A/M9□AV

D-A9□/A9□V

D-Y59□/Y69□/Y7P/Y7PV


D-Y7□W/Y7□WV/Y7BA

D-Z7□/Z80



D-A5□/A6□


D-A59W



D-F5□/J59


D-F5□W/J59W/F5BA

D-F59F/F5NT




D-P3DWA

D-P3DW



D-P4DW



Standard	Double Acting, Single Rod	MB
Double Acting, Double Rod	MBW	
Non-rotating Rod	Double Acting, Single Rod	MBK
Double Acting, Double Rod	MBKW	
With End Lock	MBB	
Low Friction	MB□Q	
Auto Switch		
Made to Order		

## Auto Switch Proper Mounting Position (Detection at stroke end) and Its Mounting Height

### Auto Switch Proper Mounting Position (Standard type)

[mm]

Auto switch model Bore size	D-M9□ D-M9□V D-M9□W D-M9□WV D-M9□A D-M9□AV		D-A9□ D-A9□V		D-F5□ D-J59 D-F59F		D-F5NT		D-A5□ D-A6□		D-A59W		D-G39 D-K39 D-A3□ D-A44		D-Y59□ D-Y69□ D-Y7P D-Y7PV D-Y7H D-Y7□W D-Y7□WV D-Z7□ D-Z8□		D-P3DWA D-P3DW Note 1)		D-P4DW	
	A	B	A	B	A	B	A	B	A	B	A	B	A	B	A	B	A	B	A	B
32	10	8	6	4	6.5	4.5	11.5	9.5	0	0	4	2	0	0	3.5	1.5	5.5	3.5	3	1
40	9	9	5	5	5.5	5.5	10.5	10.5	0	0	3	3	0	0	2.5	2.5	4.5	4.5	2	2
50	10	9	6	5	6.5	5.5	11.5	10.5	0	0	4	3	0	0	3.5	2.5	5.5	4.5	3	2
63	10	9	6	5	6.5	5.5	11.5	10.5	0	0	4	3	0	0	3.5	2.5	5.5	4.5	3	2
80	14.5	11.5	10.5	7.5	11	8	16	13	4.5	1.5	8.5	5.5	4.5	1.5	8	5	10	7	7.5	4.5
100	14	12	10	8	10.5	8.5	15.5	13.5	4	2	8	6	4	2	7.5	5.5	9.5	7.5	7	5
125	16	16	12	12	12.5	12.5	17.5	17.5	6	6	10	10	6	6	9.5	9.5	11.5	11.5	9	9

\* Models with rubber bumper have different dimensions for auto switch proper mounting positions (A and B). Add the following values to both A and B: 3 mm (ø32 and 40), 4 mm (ø50 and 63), 5 mm (ø80 and 100), 6 mm (ø125).

Note) Adjust the auto switch after confirming the operating conditions in the actual setting.

Note 1) For ø32, the values are for the D-P3DW.

### Auto Switch Proper Mounting Height (Standard type)

[mm]

Auto switch model Bore size	D-M9□ D-M9□W D-M9□A D-A9□		D-A9□V		D-M9□V D-M9□WV D-M9□AV		D-F5□ D-J59 D-F59F D-F5□W D-J59W D-F5BA D-F5NT		D-A5□ D-A6□ D-A59W		D-G39 D-K39 D-A3□		D-A44		D-Y59□ D-Y7P D-Y7□W D-Y7BA D-Z7□ D-Z80		D-Y69□ D-Y7PV D-Y7□WV		D-P3DWA D-P3DW Note 1)		D-P4DW	
	Hs	Ht	Hs	Ht	Hs	Ht	Hs	Ht	Hs	Ht	Hs	Ht	Hs	Ht	Hs	Ht	Hs	Ht	Hs	Ht	Hs	Ht
32	24.5	23	27.5	23	30.5	23	32.5	25	35	24.5	67	27.5	77	27.5	25.5	23	26.5	23	34	23	38	31
40	28.5	25.5	31.5	25.5	34	25.5	36.5	27.5	38.5	27.5	71.5	27.5	81.5	27.5	29.5	26	30	26	39	25.5	42	33
50	33.5	31	36	31	38.5	31	41	34	43.5	34.5	77	—	87	—	33.5	31	34.5	31	43	31	46.5	39
63	38.5	36	40.5	36	43	36	46	39	48.5	39.5	83.5	—	93.5	—	39	36	40	36	48	36	51.5	44
80	46.5	45	49	45	52	45	52.5	46.5	55	46.5	92.5	—	103	—	47.5	45	48.5	45	56.5	45	58	51.5
100	54	53.5	57	53.5	59.5	53.5	59.5	55	62	55	103	—	113.5	—	55.5	53.5	56.5	53.5	64.5	53.5	65.5	60.5
125	65.5	64.5	68.5	64.5	71	64.5	70.5	66.5	71.5	66.5	115	—	125	—	67.5	65	68.5	65	76	64.5	76.5	72

Note 1) For ø32, the values are for the D-P3DW.

## Auto Switch Proper Mounting Position (Detection at stroke end) and Its Mounting Height

### Auto Switch Proper Mounting Position (Non-rotating rod type, With end lock)

[mm]

Auto switch model Bore size	D-M9□ D-M9□V D-M9□W D-M9□WV D-M9□A D-M9□AV		D-A9□ D-A9□V		D-F5□ D-J59 D-F59F		D-F5NT		D-A5□ D-A6□		D-A59W		D-G39 D-K39 D-A3□ D-A44		D-Y59□ D-Y69□ D-Y7P D-Y7PV D-Y7H D-Y7□W D-Y7□WV D-Z7□ D-Z8□		D-P3DWA D-P3DW Note 1)		D-P4DW	
	A	B	A	B	A	B	A	B	A	B	A	B	A	B	A	B	A	B	A	B
32	10.5	8	6.5	4	7	4.5	12	9.5	0.5	0	4.5	2	0.5	0	4	1.5	6	3.5	3.5	1
40	10.5	8	6.5	4	7	4.5	12	9.5	0.5	0	4.5	2	0.5	0	4	1.5	6	3.5	3.5	1
50	11	8.5	7	4.5	7.5	5	12.5	10	1	0	5	2.5	1	0	4.5	2	6.5	4	4	1.5
63	11	8.5	7	4.5	7.5	5	12.5	10	1	0	5	2.5	1	0	4.5	2	6.5	4	4	1.5
80	14	12.5	10	8.5	10.5	9	15.5	14	4	2.5	8	6.5	4	2.5	7.5	6	9.5	8	7	5.5
100	14	12.5	10	8.5	10.5	9	15.5	14	4	2.5	8	6.5	4	2.5	7.5	6	9.5	8	7	5.5

\* Models with rubber bumper have different dimensions for auto switch proper mounting positions (A and B). Add the following values to both A and B: 3 mm (ø32 and 40), 4 mm (ø50 and 63), 5 mm (ø80 and 100).

Note) Adjust the auto switch after confirming the operating conditions in the actual setting.

Note 1) For ø32, the values are for the D-P3DW.

### Auto Switch Proper Mounting Height (Non-rotating rod type, With end lock)

[mm]

Auto switch model Bore size	D-M9□ D-M9□W D-M9□A D-A9□		D-A9□V		D-M9□V D-M9□WV D-M9□AV		D-F5□ D-J59 D-F59F D-F5□W D-J59W D-F5BA D-F5NT		D-A5□ D-A6□ D-A59W		D-G39 D-K39 D-A3□		D-A44		D-Y59□ D-Y7P D-Y7□W D-Y7BA D-Z7□ D-Z80		D-Y69□ D-Y7PV D-Y7□WV		D-P3DWA D-P3DW Note 1)		D-P4DW	
	Hs	Ht	Hs	Ht	Hs	Ht	Hs	Ht	Hs	Ht	Hs	Ht	Hs	Ht	Hs	Ht	Hs	Ht	Hs	Ht	Hs	Ht
32	24.5	23	27.5	23	30.5	23	32.5	25	35	24.5	67	27.5	77	27.5	25.5	23	26.5	23	34	23	38	31
40	28.5	25.5	31.5	25.5	34	25.5	36.5	27.5	38.5	27.5	71.5	27.5	81.5	27.5	29.5	26	30	26	39	25.5	42	33
50	33.5	31	36	31	38.5	31	41	34	43.5	34.5	77	—	87	—	33.5	31	34.5	31	43	31	46.5	39
63	38.5	36	40.5	36	43	36	46	39	48.5	39.5	83.5	—	93.5	—	39	36	40	36	48	36	51.5	44
80	46.5	45	49	45	52	45	52.5	46.5	55	46.5	92.5	—	103	—	47.5	45	48.5	45	56.5	45	58	51.5
100	54	53.5	57	53.5	59.5	53.5	59.5	55	62	55	103	—	113.5	—	55.5	53.5	56.5	53.5	64.5	53.5	65.5	60.5

Note 1) For ø32, the values are for the D-P3DW.

Standard	Double Acting, Single Rod	<b>MB</b>
Standard	Double Acting, Double Rod	<b>MBW</b>
Non-rotating Rod	Double Acting, Single Rod	<b>MBK</b>
Non-rotating Rod	Double Acting, Double Rod	<b>MBKW</b>
With End Lock		<b>MBB</b>
Low Friction		<b>MB□Q</b>

Auto Switch

Made to Order

## Minimum Stroke for Auto Switch Mounting

### Mounting Brackets Except Center Trunnion

n: Number of auto switches [mm]

Auto switch model	Number of auto switches	ø32, ø40, ø50, ø63	ø80, ø100	ø125 <small>Note 2)</small>
<b>D-M9□</b> <b>D-M9□W</b>	2 (Different surfaces, same surface) 1	15		
	n	$15 + 40 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>		
<b>D-M9□V</b> <b>D-M9□WV</b>	2 (Different surfaces, same surface) 1	10		
	n	$10 + 30 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>		
<b>D-M9□A</b>	2 (Different surfaces, same surface) 1	15		
	n	$15 + 40 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>		
<b>D-M9□AV</b>	2 (Different surfaces, same surface) 1	15		
	n	$15 + 30 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>		
<b>D-A9□</b>	2 (Different surfaces, same surface) 1	15		
	n	$15 + 40 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>		
<b>D-A9□V</b>	2 (Different surfaces, same surface) 1	10		
	n	$10 + 30 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>		
<b>D-G39</b> <b>D-K39</b> <b>D-A3□</b>	2 (Different surfaces)	35		
	2 (Same surface)	100		
	n (Different surfaces)	$35 + 30 (n-2)$ (n = 2, 3, 4...) <small>Note 1)</small>		
	n (Same surface)	$100 + 100 (n-2)$ (n = 2, 3, 4...) <small>Note 1)</small>		
	1	10		
<b>D-A44</b>	2 (Different surfaces)	35		
	2 (Same surface)	55		
	n (Different surfaces)	$35 + 30 (n-2)$ (n = 2, 3, 4...) <small>Note 1)</small>		
	n (Same surface)	$55 + 50 (n-2)$ (n = 2, 3, 4...) <small>Note 1)</small>		
	1	10		
<b>D-F5□</b> <b>D-J59</b> <b>D-F5□W</b> <b>D-J59W</b> <b>D-F5BA</b> <b>D-F59F</b>	2 (Different surfaces, same surface) 1	15	25	25
	n (Same surface)	$15 + 55 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>	$25 + 55 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>	$25 + 55 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>
	1	10	25	25
<b>D-A5□</b> <b>D-A6□</b>	2 (Different surfaces, same surface) 1	15	20	20
	n (Different surfaces)	$15 + 55 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>	$20 + 55 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>	$20 + 55 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>
<b>D-A59W</b>	2 (Different surfaces, same surface)	20	25	25
	n (Same surface)	$20 + 55 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>	$25 + 55 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>	$25 + 55 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>
	1	15	25	25
<b>D-F5NT</b>	2 (Different surfaces, same surface)	15	25	30
	n (Same surface)	$15 + 55 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>	$25 + 55 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>	$30 + 55 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>
	1	10	25	30
<b>D-Y59□</b> <b>D-Y7P</b> <b>D-Y7□W</b> <b>D-Z7□</b> <b>D-Z80</b>	2 (Different surfaces, same surface) 1	15		
	n	$15 + 40 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>		

Note 1) When "n" is an odd number, an even number that is one larger than this odd number is used for the calculation.

Note 2) Non-rotating rod type and with end lock are applicable to ø32 to ø100.



## Minimum Stroke for Auto Switch Mounting

### Mounting Brackets Except Center Trunnion

n: Number of auto switches [mm]

Auto switch model	Number of auto switches	ø32	ø40	ø50, ø63	ø80, ø100	ø125 <small>Note 3)</small>
<b>D-Y69□</b> <b>D-Y7PV</b> <b>D-Y7□WV</b>	2 (Different surfaces, same surface) 1	10				
	n	$10 + 30 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>				
<b>D-Y7BA</b>	2 (Different surfaces, same surface) 1	20				
	n	$20 + 45 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>				
<b>D-P3DWA</b>	2 (Different surfaces, same surface) 1	—	15			
	n	—	$15 + 50 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>			
<b>D-P3DW</b>	2 (Different surfaces), 1	15	—			
	2 (Same surface)	40	—			
	n (Different surfaces)	$15 + 50 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>	—			
	n (Same surface)	$40 + 50 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>	—			
<b>D-P4DW</b>	2 (Different surfaces, same surface) 1	15				20
	n	$15 + 65 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>				$20 + 65 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <small>Note 1)</small>

Note 1) When "n" is an odd number, an even number that is one larger than this odd number is used for the calculation.

Note 3) Non-rotating rod type and with end lock are applicable to ø32 to ø100.

### Center Trunnion

n: Number of auto switches [mm]

Auto switch model	Number of auto switches	ø32	ø40	ø50	ø63	ø80	ø100	ø125 <small>Note 3)</small>
<b>D-M9□</b> <b>D-M9□W</b>	2 (Different surfaces, same surface) 1	75	80	85	90	95	105	
	n	$75 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$80 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$85 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$90 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$95 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$105 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	
<b>D-M9□V</b> <b>D-M9□WV</b>	2 (Different surfaces, same surface) 1	50	55	60	65	70	80	
	n	$50 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$55 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$60 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$65 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$70 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$80 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	
<b>D-M9□A</b>	2 (Different surfaces, same surface) 1	80	85	90	95	100	110	
	n	$80 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$85 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$90 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$95 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$100 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$110 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	
<b>D-M9□AV</b>	2 (Different surfaces, same surface) 1	55	60	65	70	75	85	
	n	$55 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$60 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$65 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$70 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$75 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$85 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	
<b>D-A9□</b>	2 (Different surfaces, same surface) 1	70	75	80	85	95	100	
	n	$70 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$75 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$80 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$85 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$95 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$100 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	
<b>D-A9□V</b>	2 (Different surfaces, same surface) 1	45	50	55	60	70	75	
	n	$45 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$50 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$55 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$60 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$70 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	$75 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <small>Note 2)</small>	

Note 2) When "n" is an odd number, a multiple of 4 that is larger than this odd number is used for the calculation.

Note 3) Non-rotating rod type and with end lock are applicable to ø32 to ø100.

Standard	Double Acting, Single Rod	<b>MB</b>
Standard	Double Acting, Double Rod	<b>MBW</b>
Non-rotating Rod	Double Acting, Single Rod	<b>MBK</b>
Non-rotating Rod	Double Acting, Double Rod	<b>MBKW</b>
With End Lock		<b>MBB</b>
Low Friction		<b>MB□Q</b>
Auto Switch		
Made to Order		

## Minimum Stroke for Auto Switch Mounting

### Center Trunnion

n: Number of auto switches [mm]

Auto switch model	Number of auto switches	ø32	ø40	ø50	ø63	ø80	ø100	ø125 <sup>Note 3)</sup>
<b>D-G39</b> <b>D-K39</b> <b>D-A3□</b>	2 (Different surfaces)	60	65	75	80	85	90	
	2 (Same surface)	90	95	100	105	110	125	
	n (Different surfaces)	$60 + 30 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>	$65 + 30 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>	$75 + 30 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>	$80 + 30 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>	$85 + 30 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>	$90 + 30 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>	
	n (Same surface)	$90 + 100 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>	$95 + 100 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>	$100 + 100 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>	$105 + 100 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>	$110 + 100 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>	$125 + 100 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>	
	1	60	65	75	80	85	90	
<b>D-A44</b>	2 (Different surfaces)	70	75	80	85	90		
	2 (Same surface)	70	75	80	85	90		
	n (Different surfaces)	$70 + 30 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>	$75 + 30 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>	$80 + 30 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>	$85 + 30 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>	$90 + 30 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>		
	n (Same surface)	$70 + 50 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>	$75 + 50 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>	$80 + 50 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>	$85 + 50 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>	$90 + 50 \frac{(n-2)}{2}$ (n = 2, 4, 6, 8...) <sup>Note 1)</sup>		
	1	70	75	80	85	90		
<b>D-F5□/J59</b> <b>D-F5□W</b> <b>D-J59W</b> <b>D-F5BA</b> <b>D-F59F</b>	2 (Different surfaces, same surface)	90	95	110	115	120	130	
	n (Same surface)	$90 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$95 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$110 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$115 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$120 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$130 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	
	1	90	95	110	115	120	130	
	n (Same surface)	$100 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$105 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$120 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$125 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$130 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$140 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	
<b>D-F5NT</b>	2 (Different surfaces, same surface)	100	105	120	125	130	140	
	n (Same surface)	$100 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$105 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$120 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$125 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$130 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$140 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	
	1	100	105	120	125	130	140	
<b>D-A5□</b> <b>D-A6□</b>	2 (Different surfaces, same surface)	60	80	105	110	115		
	1	60	80	105	110	115		
<b>D-A59W</b>	n (Same surface)	$60 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$80 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$105 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$110 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$115 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$120 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	
	1	60	70	85	110	115	120	
	n (Same surface)	$60 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$70 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$85 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$110 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$115 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$120 + 55 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	
<b>D-Y59□</b> <b>D-Y7P</b> <b>D-Y7□W</b> <b>D-Z7□</b> <b>D-Z80</b>	2 (Different surfaces, same surface)	80	85	90	95	100	105	
	1	80	85	90	95	100	105	
	n	$80 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$85 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$90 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$95 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$100 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$105 + 40 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	
<b>D-Y69□</b> <b>D-Y7PV</b> <b>D-Y7□WV</b>	2 (Different surfaces, same surface)	60	65	70	75	85	85	
	1	60	65	70	75	85	85	
<b>D-Y7BA</b>	n	$60 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$65 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$70 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$75 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$85 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$85 + 30 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	
	1	85	90	100	105	110	115	
<b>D-P3DWA</b>	n	$85 + 45 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$90 + 45 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$100 + 45 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$105 + 45 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$110 + 45 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$115 + 45 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	
	1	85	90	100	105	110	115	
<b>D-P3DW</b>	n	80	85	90	95	100		
	1	80	85	90	95	100		
<b>D-P4DW</b>	n	$80 + 50 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$85 + 50 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$90 + 50 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$95 + 50 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$100 + 50 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$105 + 50 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	
	1	80	85	90	95	100		
<b>D-P3DWA</b>	n	85	90	100	105	110	115	
	1	85	90	100	105	110	115	
<b>D-P3DW</b>	n	80	85	90	95	100		
	1	80	85	90	95	100		
<b>D-P4DW</b>	n	$120 + 65 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$130 + 65 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$140 + 65 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>	$150 + 65 \frac{(n-4)}{2}$ (n = 4, 8, 12, 16...) <sup>Note 2)</sup>			
	1	120	130	140	150			

Note 1) When "n" is an odd number, an even number that is one larger than this odd number is used for the calculation.

Note 2) When "n" is an odd number, a multiple of 4 that is larger than this odd number is used for the calculation.

Note 3) Non-rotating rod type and with end lock are applicable to ø32 to ø100.

**Auto Switch Mounting Brackets/Part No.**

Auto switch model	Bore size [mm]						
	ø32	ø40	ø50	ø63	ø80	ø100	ø125
D-M9□/M9□V D-M9□W/M9□WV D-M9□A/M9□AV D-A9□/A9□V	BMB5-032	BMB5-032	BA7-040	BA7-040	BA7-063	BA7-063	BA7-080
D-A3□/A44 D-G39/K39	BMB2-032	BMB2-040	BMB1-050	BMB1-063	BMB1-080	BMB1-100	BS1-125
D-F5□/J59 D-F5□W/J59W D-F59F/F5BA D-F5NT D-A5□/A6□/A59W	BT-03	BT-03	BT-05	BT-05	BT-06	BT-06	BT-08
D-P3DWA	—	BA10-040S	BA10-050S	BA10-050S	BA10-063S	BA10-063S	BA10-080S
D-P3DW	BMB9-032S	—	—	—	—	—	—
D-P4DW	BMB3T-040	BMB3T-040	BMB3T-050	BMB3T-050	BMB3T-080	BMB3T-080	BAP2T-080
D-Y59□/Y69□ D-Y7P/Y7PV D-Y7□W/Y7□WV D-Y7BA D-Z7□/Z80	BMB4-032	BMB4-032	BMB4-050	BMB4-050	BA4-063	BA4-063	BA4-080

**[Stainless Steel Mounting Screw]**


The following stainless steel mounting screw kit (including set screws) is available. Use it in accordance with the operating environment. (Since the auto switch mounting bracket is not included, order it separately.)

BBA1: For D-A5/A6/F5/J5 types

Note 1) Refer to the **WEB catalog** or the Best Pneumatics No. 2 for details on the BBA1.

The above stainless steel screws are used when a cylinder is shipped with the D-F5BA auto switch. When only one auto switch is shipped independently, the BBA1 is attached.

Note 2) When using the D-M9□(V) or Y7BA, do not use the steel set screws which are included with the auto switch mounting brackets above (BMB5-032, BA7-□□□, BMB4-□□□, BA4-□□□). Order a stainless steel screw kit (BBA1) separately, and use the M4 x 6 L stainless steel set screws included in the BBA1.



• The figure shows the mounting example for the D-M9□(V)/M9□W(V)/M9□A(V)/A9□(V).

**Operating Range**

Auto switch model	Bore size [mm]						
	32	40	50	63	80	100	125
D-M9□/M9□V D-M9□W/M9□WV D-M9□A/M9□AV	4	4.5	4.5	4.5	5	6	7
D-Y59□/Y69□ D-Y7P/Y7□V D-Y7□W/Y7□WV D-Y7BA	5.5	5.5	7	7.5	6.5	5.5	7
D-F5□/J59 D-F5□W/J59W D-F5BA/F5NT D-F59F	3.5	4	4	4.5	4.5	4.5	5
D-G39/K39	9	9	9	10	10	11	11
D-P3DWA	—	4.5	4.5	5	5	5.5	6.5
D-P3DW	4.5	—	—	—	—	—	—
D-P4DW	4	4	4	4.5	4	4.5	4.5
D-A9□/A9□V	7	7.5	8.5	9.5	9.5	10.5	12
D-Z7□/Z80	7.5	8.5	7.5	9.5	9.5	10.5	13
D-A5□/A6□	9	9	10	11	11	11	10
D-A59W	13	13	13	14	14	15	17
D-A3□/A44	9	9	10	11	11	11	10

\* Values which include hysteresis are for guideline purposes only, they are not a guarantee (assuming approximately ±30% dispersion) and may change substantially depending on the ambient environment.

Other than the applicable auto switches listed in “How to Order”, the following auto switches are mountable.

Refer to the **WEB catalog** or the Best Pneumatics No. 2 for the detailed specifications.

Type	Model	Electrical entry	Features
Solid state	D-M9NV/M9PV/M9BV	Grommet (Perpendicular)	—
	D-Y69A/Y69B/Y7PV		—
	D-M9NWV/M9PWV/M9BWV		Diagnostic indication (2-color indication)
	D-Y7NWV/Y7PWV/Y7BWV		Water resistant (2-color indication)
	D-M9NAV/M9PAV/M9BAV		Magnetic field resistant (2-color indication)
	D-P4DW		—
	D-F59/F5P/J59	Grommet (In-line)	—
	D-Y59A/Y59B/Y7P		—
	D-Y7H		Diagnostic indication (2-color indication)
	D-F59W/F5PW/J59W		Water resistant (2-color indication)
	D-Y7NW/Y7PW/Y7BW		With timer
	D-F5BA/Y7BA		Magnetic field resistant (2-color indication)
	D-F5NT		—
	D-P5DW		—
Reed	D-A93V/A96V	Grommet (Perpendicular)	Without indicator light
	D-A90V	Grommet (In-line)	—
	D-A53/A56/Z73/Z76		Without indicator light
	D-A67/Z80		

\* With pre-wired connector is also available for solid state switches. For details, refer to the **WEB catalog** or the Best Pneumatics No. 2.


\* Normally closed (NC = b contact) solid state auto switches (D-F9G/F9H/Y7G/Y7H) are also available. For details, refer to the **WEB catalog** or the Best Pneumatics No. 2.

# Prior to Use


## Auto Switch Connection and Example

### Sink Input Specifications

#### 3-wire, NPN




#### 2-wire




### Source Input Specifications

#### 3-wire, PNP



#### 2-wire




Connect according to the applicable PLC input specifications, as the connection method will vary depending on the PLC input specifications.

### Example of AND (Series) and OR (Parallel) Connection


\* When using solid state auto switches, ensure the application is set up so the signals for the first 50 ms are invalid.

#### 3-wire AND connection for NPN output


(Using relays)



(Performed with auto switches only)




#### 3-wire OR connection for NPN output




#### 3-wire AND connection for PNP output


(Using relays)




(Performed with auto switches only)



#### 3-wire OR connection for PNP output



#### 2-wire AND connection




When two auto switches are connected in series, a load may malfunction because the load voltage will decline when in the ON state. The indicator lights will light up when both of the auto switches are in the ON state. Auto switches with load voltage less than 20 V cannot be used.

$$\begin{aligned} \text{Load voltage at ON} &= \text{Power supply voltage} - \\ &\quad \text{Residual voltage} \times 2 \text{ pcs.} \\ &= 24 \text{ V} - 4 \text{ V} \times 2 \text{ pcs.} \\ &= 16 \text{ V} \end{aligned}$$

Example: Power supply is 24 VDC  
Internal voltage drop in auto switch is 4 V.

#### 2-wire OR connection



(Solid state)  
When two auto switches are connected in parallel, malfunction may occur because the load voltage will increase when in the OFF state.

(Reed)  
Because there is no current leakage, the load voltage will not increase when turned OFF. However, depending on the number of auto switches in the ON state, the indicator lights may sometimes grow dim or not light up, due to the dispersion and reduction of the current flowing to the auto switches.

$$\begin{aligned} \text{Load voltage at OFF} &= \text{Leakage current} \times 2 \text{ pcs.} \times \\ &\quad \text{Load impedance} \\ &= 1 \text{ mA} \times 2 \text{ pcs.} \times 3 \text{ k}\Omega \\ &= 6 \text{ V} \end{aligned}$$

Example: Load impedance is 3 k $\Omega$ .  
Leakage current from auto switch is 1 mA.



Please contact SMC for detailed specifications, delivery and prices.

## Simple Specials

The following special specifications can be ordered as a simplified Made-to-Order. There is a specification sheet available on paper and CD-ROM. Please contact your SMC sales representatives if necessary.

Symbol	Specifications	MB (Standard type) Double acting					
		Single rod				Double rod	
		Air		Rubber		Air	
		ø32 to ø100	ø125	ø32 to ø100	ø125	ø32 to ø100	ø125
-XA0 to 30	Change of rod end shape	●	●	●	●	●	●
-XC14	Change of trunnion bracket mounting position	●	●	●	●	●	●

## Made to Order

Symbol	Specifications	MB (Standard type) Double acting					
		Single rod				Double rod	
		Air		Rubber		Air	
		ø32 to ø100	ø125	ø32 to ø100	ø125	ø32 to ø100	ø125
-XB5	Oversized rod cylinder <small>Note 1)</small>	●					
-XB6	Heat resistant cylinder (-10 to 150°C)	●	●			●	
-XB13	Low Speed Cylinder (5 to 50 m/s) <small>Note 1)</small>	●		●			
-XC3	Special port location <small>Note 1)</small>	●		●		●	
-XC4	With heavy duty scraper	●		●		●	
-XC5	Heat resistant cylinder (-10 to 110°C)	●	●			●	
-XC6	Made of stainless steel <small>Note 1)</small>		●		●		●
-XC7	Tie-rod, cushion valve, tie-rod nut, etc. made of stainless steel	●		●		●	
-XC8	Adjustable stroke cylinder/Adjustable extension type	●		●			
-XC9	Adjustable stroke cylinder/Adjustable retraction type	●		●			
-XC10	Dual stroke cylinder/Double rod type	●		●			
-XC11	Dual stroke cylinder/Single rod type	●		●			
-XC12	Tandem cylinder	●		●			
-XC22	Fluororubber seal	●	●	●	●	●	
-XC26	With split pins for double clevis pin/double knuckle joint pin and flat washers		●		●		
-XC27	Double clevis and double knuckle joint pins made of stainless steel	●	●	●	●		
-XC29	Double knuckle joint with spring pin	●		●			
-XC30	Rod trunnion	●		●		●	
-XC35	With coil scraper	●		●		●	
-XC65	Made of stainless steel (Combination of XC7 and XC68)	●		●			
-XC68	Made of stainless steel (with hard chrome plated piston rod)	●		●		●	
-XC88	Spatter resistant coil scraper, Lube-retainer, Grease for welding (Piston rod: Stainless steel 304)	●		●		●	
-XC89	Spatter resistant coil scraper, Lube-retainer, Grease for welding (Piston rod: S45C)	●		●		●	
-XC91	Spatter resistant coil scraper, Grease for welding (Piston rod: S45C)	●		●		●	
-X1184	Cylinder with heat resistant reed auto switch (-10 to 120°C)	●					

Note 1) The cover shape is the same as the current product.

Note 2) For details, refer to the **WEB catalog**.



MB (Standard type)		MBK (Non-rotating rod type) Double acting				MBB <sup>Note 1)</sup> (With end lock)
Double rod		Single rod		Double rod		Single rod
Rubber		Air	Rubber	Air	Rubber	Air
ø32 to ø100	ø125					

●	●	●	●			●
●	●	●	●			●

Symbol	Page
-XA0 to 30	49, 50
-XC14	50

MB (Standard type)		MBK (Non-rotating rod type) Double acting				MBB (With end lock)
Double rod		Single rod		Double rod		Single rod
Air	Rubber	Air	Rubber	Air	Rubber	Air
ø32 to ø100	ø125					

●		●	●			
●						
●		●	●	●	●	
		●	●	●	●	
		●	●			
		●	●			
●						
		●	●			●
●		●	●	●	●	●
●						
●						
●						
●						
●						
●						

Symbol	Page
-XB5	51
-XB6	51
-XB13	52
-XC3	52
-XC4	53
-XC5	53
-XC6	53
-XC7	54
-XC8	54
-XC9	55
-XC10	56
-XC11	57
-XC12	58
-XC22	58
-XC26	59
-XC27	59
-XC29	60
-XC30	60
-XC35	60
-XC65	61
-XC68	61
-XC88	61
-XC89	62
-XC91	62
-X1184	63

Standard	Double Acting, Single Rod	<b>MB</b>
	Double Acting, Double Rod	<b>MBW</b>
Non-rotating Rod	Double Acting, Single Rod	<b>MBK</b>
	Double Acting, Double Rod	<b>MBKW</b>
With End Lock		<b>MBB</b>
Low Friction		<b>MB□Q</b>
		<b>Auto Switch</b>
		<b>Made to Order</b>

# Series MB Simple Specials

These changes are dealt with Simple Specials System.

For details, refer to the Simple Specials  
System in the WEB catalog.  
<http://www.smcworld.com>

Symbol

## 1 Change of Rod End Shape

-XA0 to XA30

Series		Action	Symbol for change of rod end shape	Note
Standard type	MB	Double acting, Single rod	XA0 to 30	Except pivot bracket and rod end bracket
	MBW	Double acting, Double rod	XA0 to 30	Except pivot bracket and rod end bracket
Non-rotating rod type	MBK	Double acting, Single rod	XA0, 1, 6, 10, 11, 13, 14, 17, 19, 21	
With end lock	MBB	Double acting, Single rod	XA0 to 30	

### Precautions

- SMC will make appropriate arrangements if no dimension, tolerance, or finish instructions are given in the diagram.
- Standard dimensions marked with "\*" will be as follows to the rod diameter (D). Enter any special dimension you desire.
- $D \leq 6 \rightarrow D - 1 \text{ mm}$      $6 < D \leq 25 \rightarrow D - 2 \text{ mm}$      $D > 25 \rightarrow D - 4 \text{ mm}$   
 3. In the case of double rod type and single acting retraction type, enter the dimensions when the rod is retracted.

<b>Symbol: A0</b> 	<b>Symbol: A1</b> 	<b>Symbol: A2</b> 	<b>Symbol: A3</b> 
<b>Symbol: A4</b> 	<b>Symbol: A5</b> 	<b>Symbol: A6</b> 	<b>Symbol: A7</b> 
<b>Symbol: A8</b> 	<b>Symbol: A9</b> 	<b>Symbol: A10</b> 	<b>Symbol: A11</b> 
<b>Symbol: A12</b> 	<b>Symbol: A13</b> 	<b>Symbol: A14</b> 	<b>Symbol: A15</b> 
<b>Symbol: A16</b> 	<b>Symbol: A17</b> 	<b>Symbol: A18</b> 	<b>Symbol: A19</b> 

<b>Symbol: A20</b> 	<b>Symbol: A21</b> 	<b>Symbol: A22</b> 	<b>Symbol: A23</b> 
<b>Symbol: A24</b> 	<b>Symbol: A25</b> 	<b>Symbol: A26</b> 	<b>Symbol: A27</b> 
<b>Symbol: A28</b> 	<b>Symbol: A29</b> 	<b>Symbol: A30</b> 	

Standard	Double Acting, Single Rod	<b>MB</b>
Standard	Double Acting, Double Rod	<b>MBW</b>
Non-rotating Rod	Double Acting, Single Rod	<b>MBK</b>
Non-rotating Rod	Double Acting, Double Rod	<b>MBKW</b>


## 2 Change of Trunnion Bracket Mounting Position **Symbol -XC14**

The position for mounting the trunnion pivot bracket on the cylinder can be moved from the standard mounting position to any desired position.

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	
	MBW	Double acting, Double rod	
Non-rotating rod type	MBK	Double acting, Single rod	
With end lock	MBB	Double acting, Single rod	

### Precautions

- Specify "Z + 1/2 stroke" in the case the trunnion bracket position is not -XC14A, B or trunnion is not a center trunnion.
- SMC will make appropriate arrangements if no dimension, tolerance, or finish instructions are given in the diagram.
- The possible range of trunnion bracket mounting position is indicated in the table below.
- Some trunnion mounting positions do not allow auto switch mounting. Please consult with SMC for more information.



With End Lock	<b>MBB</b>
Low Friction	<b>MBQ</b>

Bore size	Symbol	Z + 1/2 stroke				
		For -XC14A	For -XC14B	For -XC14		Reference Standard (Center trunnion)
				Minimum	Maximum	
32		82.5	95.5 + Stroke	84	94 + Stroke	89 + 1/2 stroke
40		89	97 + Stroke	90	96 + Stroke	93 + 1/2 stroke
50		100.5	109.5 + Stroke	102	108 + Stroke	105 + 1/2 stroke
63		103.5	106.5 + Stroke	105	105 + Stroke	105 + 1/2 stroke
80		127	131 + Stroke	128	130 + Stroke	129 + 1/2 stroke
100		130	128 + Stroke	131	127 + Stroke	129 + 1/2 stroke
125		160	154 + Stroke	160.5	153.5 + Stroke	157 + 1/2 stroke

Auto Switch	<b>MBQ</b>
Made to Order	

# Series MB

## Made to Order

Please contact SMC for detailed dimensions, specifications and lead times.



### 1 Oversized Rod Cylinder

Symbol  
**-XB5**

A cylinder that has been made stronger through the use of a piston rod with a larger diameter. It is used for long stroke applications that pose the risk of bending or buckling of the piston rod. (Please contact SMC if a lateral load must be applied to it.)

#### Applicable Series


Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	Except ø125

Note) The cover shape is the same as the current product.

#### How to Order

**MB** **Mounting style** **Bore size** – **Stroke** – **XB5**  
Oversized rod cylinder

#### Dimensions (Dimensions other than below are the same as standard type.)



Bore size	A	Effective thread length	B1	øD	H	H1	K	Width across flats	MN	W	ZZ
32	30	27	22	16	51	8	6	14	M14 x 1.5	7.2	139
40	35	32	27	20	58	11	7	18	M18 x 1.5	9.7	146
50	40	37	32	25	68	13	10	22	M22 x 1.5	10.5	166
63	40	37	32	25	68	13	10	22	M22 x 1.5	12	166
80	40	37	41	30	74	16	10	26	M26 x 1.5	14	192
100	50	47	46	36	90	18	16	31	M30 x 1.5	15	208

### 2 Heat Resistant Cylinder (–10 to 150°C)

Symbol  
**-XB6**

Air cylinder which changed the seal material and grease, so that it could be used even at higher temperature up to 150 from –10°C.

#### Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	Except with rubber bumper and with auto switch
	MBW	Double acting, Double rod	Except with rubber bumper and with auto switch

- Note 1) Operate without lubrication from a pneumatic system lubricator.  
 Note 2) Please contact SMC for details on the maintenance intervals for this cylinder, which differ from those of the standard cylinder.  
 Note 3) In principle, it is impossible to make built-in magnet type and the one with auto switch. But, as for the one with auto switch, and the heat resistant cylinder with heat resistant auto switch, please contact SMC.  
 Note 4) Piston speed is ranged from 50 to 500 mm/s.

#### Specifications

<b>Ambient temperature range</b>	–10°C to 150°C
<b>Seal material</b>	Fluororubber
<b>Grease</b>	Heat resistant grease
<b>Specifications other than above and external dimensions</b>	Same as standard type

#### Warning Precautions

Be aware that smoking cigarettes etc. after your hands have come into contact with the grease used in this cylinder can create a gas that is hazardous to humans.

#### How to Order

**Standard model no.** – **XB6**  
Heat resistant cylinder

### 3 Low Speed Cylinder (5 to 50 mm/s)

Symbol  
**-XB13**

Even if driving at lower speeds 5 to 50 mm/s, there would be no stick-slip phenomenon and it can run smoothly.

#### Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	Except ø125

Note) The cover shape is the same as the current product.

#### How to Order

Standard model no. **- XB13**  
Low speed cylinder

#### Specifications

Piston speed	5 to 50 mm/s
Dimensions	Same as standard type
Specifications other than above	Same as standard type

Note 1) Operate without lubrication from a pneumatic system lubricator.

Note 2) For the speed adjustment, use speed controllers for controlling at lower speeds. (Series AS-FM/AS-M)

#### Warning Precautions

Be aware that smoking cigarettes etc. after your hands have come into contact with the grease used in this cylinder can create a gas that is hazardous to humans.

### 4 Special Port Location

Symbol  
**-XC3**

Compared with the standard type, a cylinder which changes the connection port location of rod/head cover and the location of cushion valve.

#### Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	
	MBW	Double acting, Double rod	
Non-rotating rod type	MBK	Double acting, Single rod	
	MBKW	Double acting, Double rod	

Note) The cover shape is the same as the current product.

#### How to Order

MB  
MBW  
MBK  
MBKW

Mounting style Bore size - Stroke Suffix - XC3 A C

Special port location

• Cushion valve location seen from the rod side  
• Rod port location seen from the rod side

\* For port location, refer to the following diagrams and show the symbols of A, B, C and D.

Specifications: Same as standard type

#### Relationship between Port Location and Cushion Valve Location

Corresponding symbol of mounting bracket (Positional relationships)						
Basic	Axial foot	Rod flange	Head flange	Single clevis	Double clevis	Center trunnion

- Symbol of position for port and cushion valve has to be looked from the rod side, as figures above. (In the case of standard cylinders, port must be positioned in the upper side.) Define the upper side to be A, and then B, C, and D in a clockwise order.
- Model of combination between port and cushion valve is applicable only when the position of a port and a cushion valve on the rod cover and the head cover will be changed to the same position against the support bracket, as a rule.
- XC3AA is not available in terms of the position between port and cushion valve, since it is available in the standard products.

Standard Double Acting, Single Rod MB  
Double Acting, Double Rod MBW  
Non-rotating Rod Double Acting, Single Rod MBK  
Double Acting, Double Rod MBKW  
With End Lock MBB  
Low Friction MBQ  
Auto Switch  
Made to Order

## 5 With Heavy Duty Scraper

Symbol  
**-XC4**

It is suitable for using cylinders under the environment, where there are much dusts in a surrounding area by using a heavy duty scraper on the wiper ring, or using cylinders under earth and sand exposed to the die-casted equipment, construction machinery, or industrial vehicles.

### Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	Except ø125
	MBW	Double acting, Double rod	Except ø125

### How to Order

Standard model no. **- XC4**  
With heavy duty scraper


Specifications: Same as standard type

### ⚠ Caution

Do not replace heavy duty scrapers.

- Since heavy duty scrapers are press-fit, do not replace the cover only, but rather the entire rod cover assembly.

### Construction (Dimensions are the same as standard.)



	[mm]	
Bore size	H	ZZ
32	47	135
40	58	146
50	67	165
63	67	165
80	81	199
100	81	199

## 6 Heat Resistant Cylinder (−10 to 110°C)

Symbol  
**-XC5**

Cylinder which changed the seal material for heat resistance (up to 110°C) in order to use under the severe ambient temperature condition which exceeds the standard specifications of −10 to 70°C.

### Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	Except with rubber bumper and with auto switch
	MBW	Double acting, Double rod	Except ø125, with rubber bumper and with auto switch

### How to Order

Standard model no. **- XC5**  
Heat resistant cylinder

### Specifications

Ambient temperature range	−10°C to 110°C
Seal material	Fluororubber
With auto switch	Unavailable Note 2)
Specifications other than above and external dimensions	Same as standard type

Note 1) Please contact SMC for details on the maintenance intervals for this cylinder, which differ from those of the standard cylinder.

Note 2) Manufacturing built-in magnet type and the one with auto switch is impossible.

Note 3) Rod boot material is heat resistant tarpaulin.

## 7 Made of Stainless Steel

Symbol  
**-XC6**

Suitable for the cases it is likely to generate rust by being immersed in the water and corrosion.

### Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	ø125 only
	MBW	Double acting, Double rod	ø125 only
Non-rotating rod type	MBK	Double acting, Single rod	
	MBKW	Double acting, Double rod	

### How to Order

Standard model no. **- XC6**  
Made of stainless steel

### Specifications

Parts changed to stainless steel	Piston rod, Rod end nut
Max. manufacturable stroke [mm]	Double acting, Single rod: 1500 Double acting single rod with rod boot: 1000
Specifications other than above and external dimensions	Same as standard type



## 8 Tie-rod, Cushion Valve, Tie-rod Nut, etc. Made of Stainless Steel

Symbol  
**-XC7**

When using in locations where the rust generation or corrosion likelihood exists, the standard parts material have been partly changed to the stainless steel.

### Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	Except ø125
	MBW	Double acting, Double rod	Except ø125
Non-rotating rod type	MBK	Double acting, Single rod	
	MBKW	Double acting, Double rod	

### Specifications

<b>Component parts changed to stainless steel</b>	Tie-rod, Tie-rod nut, Bracket mounting bolt, Cushion valve, Lock nut
<b>Specifications other than above</b>	Same as standard type
<b>Dimensions</b>	Same as standard type

### How to Order

Standard model no. **- XC7**  
 Tie-rod, cushion valve, tie-rod nut, etc. made of stainless steel

## 9 Adjustable Stroke Cylinder/Adjustable Extension Type

Symbol  
**-XC8**

It adjusts the extending stroke by the stroke adjustable mechanism equipped in the head side. (After the stroke is adjusted, with cushion on both sides is altered to single-sided, with cushion.)

### Applicable Series


Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	Except ø125, head flange and clevis types
Non-rotating rod type	MBK	Double acting, Single rod	Except ø125, head flange and clevis types

### Specifications

Stroke adjustment symbol	A	B
<b>Stroke adjustment range [mm]</b>	0 to 25	0 to 50
<b>Specifications other than above</b>	Same as standard type	

### How to Order


**MB** **MBK** **Mounting style** **Bore size** – **Stroke** **Suffix** **Stroke adjustment symbol** **Z** – **Pivot bracket** **Rod end bracket** – **- XC8**  
 \* Except head flange and clevis types Adjustable stroke cylinder/Adjustable extension type



### Warning Precautions

- When the cylinder is operating, if something gets caught between the stopper bracket for adjusting the stroke and the cylinder body, it could cause bodily injury or damage the peripheral equipment. Therefore, take preventive measures as necessary, such as installing a protective cover.
- To adjust the stroke, make sure to secure the wrench flats of the stopper bracket by a wrench, etc. before loosening the lock nut. If the lock nut is loosened without securing the stopper bracket, be aware that the area that joins the load to the piston rod or the area in which the piston rod is joined with the load side and the stopper bracket side could loosen first. It may cause an accident or malfunction.

### Dimensions (Dimensions other than below are the same as standard type.)



10 Adjustable Stroke Cylinder/Adjustable Retraction Type

Symbol  
-XC9

The retracting stroke of the cylinder can be adjusted by the adjustment bolt.

Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	Except ø125, head flange and clevis types
Non-rotating rod type	MBK	Double acting, Single rod	Except ø125, head flange and clevis types

Specifications

Stroke adjustment symbol	A	B
Stroke adjustment range [mm]	0 to 25	0 to 50
Specifications other than above	Same as standard type	

How to Order


**MB**  
**MBK** **Mounting style** **Bore size** – **Stroke** **Suffix** **Stroke adjustment symbol** **Z** – **Pivot bracket** **Rod end bracket** – **XC9**  
\* Except head flange and clevis types  
Adjustable stroke cylinder/Adjustable retraction type

(After the stroke is adjusted, with cushion on both sides is altered to single-sided, with cushion.)

⚠ Caution  
Precautions

1. When air is supplied to the cylinder, if the stroke adjustment bolt is loosened in excess of the allowable stroke adjustment amount, be aware that the stroke adjustment bolt could fly out or air could be discharged, which could injure personnel or damage the peripheral equipment.
2. Adjust the stroke when the cylinder is not pressurized.  
If it is adjusted in the pressurized state, the seal of the adjustment section could become deformed, leading to air leakage.

Dimensions (Dimensions other than below are the same as standard type.)



Bore size	b	c	d	ka	mm	ZZ
32	9	8	40	8	M12 x 1.25	171
40	9	8	39.5	8	M12 x 1.25	174.5
50	11	8	46	13	M16 x 1.5	198
63	11	8	52	17	M20 x 1.5	204
80	15	10	61	19	M24 x 1.5	247
100	15	10	61.5	19	M24 x 1.5	247.5

# 11 Dual Stroke Cylinder/Double Rod Type

Symbol  
**-XC10**

Two cylinders are constructed as one cylinder in a back-to-back configuration allowing the cylinder stroke to be controlled in three steps.

## Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	Except ø125, clevis and trunnion types, pivot bracket and rod end bracket
Non-rotating rod type	MBK	Double acting, Single rod	Except clevis and trunnion types
With end lock	MBB	Double acting, Single rod	Except clevis and trunnion types

## Specifications

Max. manufacturable stroke [mm]	Stroke A + B = 1000
Specifications other than above	Same as standard type



## How to Order

**MB** **Mounting style** **Bore size** – **Stroke A** **Suffix** + **Stroke B** **Suffix** **Z** – **XC10**  
 \* Except clevis and trunnion types  
 Dual stroke cylinder/Double rod type


**MBK** **Mounting style** **Bore size** – **Stroke A** **Suffix** + **Stroke B** **Suffix** **Z** – **XC10**  
 \* Except clevis and trunnion types  
 Dual stroke cylinder/Double rod type

**MBB** **Mounting style** **Bore size** – **Stroke A** **Suffix** + **Stroke B** **Suffix** **Z** – **XC10**  
 \* Except clevis and trunnion types  
 Dual stroke cylinder/Double rod type

## Function



## Dimensions (Dimensions other than below are the same as standard type.)



Bore size	GC	NA	NB	S	ZZ
32	36	64	10.6	178	272
40	38	64	10.6	178	280
50	41	73	10.6	198	314
63	43	73	10.6	198	314
80	52	90	14.6	242	386
100	52	90	14.6	242	386

## 12 Dual Stroke Cylinder/Single Rod Type

Symbol  
**-XC11**

Two cylinders can be integrated by connecting them in line, and the cylinder stroke can be controlled in two stages in both directions.

### Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	Except $\phi 125$ and trunnion type

### Specifications


Max. manufacturable stroke [mm]	Stroke A + Stroke B = 1000
Specifications other than above	Same as standard type

### How to Order

MB [Mounting style] [Bore size] – [Stroke A] [Suffix] + [Stroke B-A] [Suffix] Z – [Pivot bracket] [Rod end bracket] – XC11  
 \* Except trunnion type


Dual stroke cylinder/Single rod type

### Dimensions (Dimensions other than below are the same as standard type.)




Bore size	GC	NA	NB	S	ZZ
32	36	64	10.6	179	230
40	38	64	10.6	179	234
50	41	73	10.6	199	261
63	43	73	10.6	199	261
80	52	90	14.6	243	319
100	52	90	14.6	243	319


### Functional description of dual stroke cylinder



### Stroke A or Stroke B operation can be made individually.



### Double output is possible.



### Caution Precautions

- Do not supply air until the cylinder is fixed with the attached bolt.
- If air is supplied without securing the cylinder, the cylinder could lurch, posing the risk of bodily injury or damage to the peripheral equipment.

## 13 Tandem Cylinder

Symbol  
**-XC12**

This is a cylinder produced with two air cylinders in line allowing double the output force.

### Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	Except ø125


### How to Order

Standard model no. **- XC12**  
Tandem cylinder


### Specifications

Max. manufacturable stroke [mm]	500
Specifications other than above	Same as standard type

### Function



### Dimensions (Dimensions other than below are the same as standard type.)



Bore size	GC	NA	NB	S	ZZ
32	36	64	10.6	180	231
40	38	64	10.6	180	235
50	41	73	10.6	200	262
63	43	73	10.6	200	262
80	52	90	14.6	244	320
100	52	90	14.6	244	320

## 14 Fluororubber Seal

Symbol  
**-XC22**

### Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	Air cushion only
	MBW	Double acting, Double rod	Air cushion only

### How to Order

Standard model no. **Z - XC22**  
Fluororubber seal

### Specifications

Seal material	Fluororubber
Ambient temperature range	With auto switch Note 1): -10°C to 60°C (No freezing) Without auto switch: -10°C to 70°C
Specifications other than above and external dimensions	Same as standard type

Note 1) Please contact SMC, as the type of chemical and the operating temperature may not allow the use of this product.

Note 2) Cylinders with auto switches can also be produced; however, auto switch related parts (auto switch units, mounting brackets, built-in magnets) are the same as standard products. Before using these, please contact SMC regarding their suitability for the operating environment.

Note 3) No cushion is equipped for N type.

## 15 With Split Pins for Double Clevis Pin/Double Knuckle Joint Pin and Flat Washers Symbol **-XC26**

Flat washer is added for the double clevis (one of the mounting styles) or double knuckle joint (one of the accessories).

### Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	ø125 only

### How to Order

#### • Product

**MBBD** Standard model no. **- XC26**  
 • Double clevis type  
 With clevis pin, split pin and flat washer

#### • Parts assembly

**MB - D 12 - XC26**  
 • Double clevis  
 • With clevis pin, split pin and flat washer  
 • Bore size  
12 125 mm

**Y - 12M - XC26**  
 • Double knuckle joint  
 With knuckle joint pin, split pin and flat washer


**IY - 12 - XC26**  
 • Clevis pin/Knuckle joint pin  
 With clevis pin, knuckle joint pin, split pin and flat washer

### Specifications

<b>Mounting</b>	Only double clevis type (D), double knuckle joint
<b>Changed parts</b>	Clevis pin, knuckle joint pin, flat washer
<b>Specifications other than above</b>	Same as standard type

### Dimensions (Dimensions other than below are the same as standard type.)


#### Double clevis



- \* For mounting bracket, split pin, clevis pin and flat washer are shipped together, (but not assembled).
- \* Mounting method is the same as standard type.

Bore size [mm]	CW
ø125	90

#### Double knuckle joint



- \* For mounting bracket, split pin, knuckle joint pin and flat washer are shipped together, (but not assembled).
- \* Mounting method is the same as standard type.

Bore size [mm]	L
ø125	90

## 16 Double Clevis and Double Knuckle Joint Pins Made of Stainless Steel Symbol **-XC27**

To prevent the oscillating portion of the double clevis or the double knuckle joint from rusting, the material of the pin and the retaining ring has been changed to stainless steel.

### Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	
Non-rotating rod type	MBK	Double acting, Single rod	
With end lock	MBB	Double acting, Single rod	

### Specifications

<b>Mounting style</b>	Only double clevis type (D), double knuckle joint
<b>Pin and retaining ring material</b>	Stainless steel 304
<b>Specifications other than above</b>	Same as standard type

### How to Order

**MB□D** Standard model no. **- XC27**  
 • Double clevis type  
 Double clevis pin made of stainless steel

**Y - 03M, 04M, 05M, 08M, 10M - XC27**  
 • Double knuckle joint  
 Double knuckle joint pin made of stainless steel

**CD - M03, M05, M08 - XC27**  
 • Clevis pin  
 Knuckle pin made of stainless steel



## 17 Double Knuckle Joint with Spring Pin

Symbol  
**-XC29**

To prevent loosening of the double knuckle joint of standard air cylinder (Series CM2/CA2)

### Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	Except ø125 and rod end bracket
With end lock	MBB	Double acting, Single rod	

### How to Order

Standard model no. **- XC29**  
Double knuckle joint with spring pin

Specifications: Same as standard type

## 18 Rod Trunnion

Symbol  
**-XC30**

This cylinder shortens the distance between the fulcrum and the rod end by installing a trunnion bracket in front of the rod side cover.

### Applicable Series


Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	Except ø125
	MBW	Double acting, Double rod	Except ø125
Non-rotating rod type	MBK	Double acting, Single rod	
	MBKW	Double acting, Double rod	
With end lock	MBB	Double acting, Single rod	

### How to Order

MB ☐ T Standard model no. **- XC30**  
Trunnion bracket Rod trunnion

Specifications: Same as standard type

### Dimensions (Dimensions other than below are the same as standard type.)



## 19 With Coil Scraper

Symbol  
**-XC35**

It gets rid of frost, ice, weld spatter, cutting chips adhered to the piston rod, and protects the seals etc.

### Applicable Series


Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	Except ø125
	MBW	Double acting, Double rod	Except ø125

### How to Order

Standard model no. **- XC35**  
With coil scraper

Specifications: Same as standard type

### Dimensions (Dimensions other than below are the same as standard type.)



## 20 Made of Stainless Steel (Combination of XC7 and XC68)

Symbol

**-XC65**

Suitable for the cases it is likely to generate rust by being immersed in the water and corrosion.

### Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	Except ø125
	MBW	Double acting, Double rod	Except ø125 and air cushion

### How to Order

Standard model no.	- XC65
Made of stainless steel (Combination of XC7 and XC68)	

### Specifications

Parts changed to stainless steel	Tie-rod, Tie-rod nut, Cushion valve, Piston rod (with hard chrome plated), Rod end nut
Max. manufacturable stroke [mm]	Double acting, Single rod: 1600 Double acting single rod with rod boot: 1000
Specifications other than above and external dimensions	Same as standard type

## 21 Made of Stainless Steel (With Hard Chrome Plated Piston Rod)

Symbol

**-XC68**

Suitable for the cases it is likely to generate rust by being immersed in the water and corrosion.

### Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	Except ø125
	MBW	Double acting, Double rod	Except ø125

### How to Order

Standard model no.	- XC68
Made of stainless steel (With hard chrome plated piston rod)	

### Specifications

Parts changed to stainless steel	Piston rod, Rod end nut
Max. manufacturable stroke [mm]	Double acting, Single rod: 1600 Double acting single rod with rod boot: 1000
Specifications other than above and external dimensions	Same as standard type

## 22 Spatter Resistant Coil Scraper, Lube-retainer, Grease for Welding (Piston rod: Stainless steel 304)

Symbol

**-XC88**

Reduces spatter adhesion and improves durability by the use of the coil scraper, Lube-retainer and grease for welding.

### Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	Except ø125



### How to Order

Standard model no.	- XC88
Spatter resistant coil scraper, Lube-retainer, Grease for welding (Piston rod: Stainless steel 304)	

### Specifications

Piston rod	Stainless steel 304 (With hard chrome plated)
Scraper	With coil scraper, With Lube-retainer
Grease	Grease for welding
Max. manufacturable stroke [mm]	Double acting, Single rod: 1600
Other specifications	Same as standard type

### Dimensions (Dimensions other than below are the same as standard type.)



[mm]

Bore size	F	Fd	H	ZZ
32	21	28	50	138
40	23.5	33	61	149
50	23	39.5	67	165
63	23	39.5	67	165
80	29	44.5	82	200
100	29	54	82	200

## 23 Spatter Resistant Coil Scraper, Lube-retainer, Grease for Welding (Piston rod: S45C) **-XC89**

Symbol

Reduces spatter adhesion and improves durability by the use of the coil scraper, Lube-retainer and grease for welding.

### Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	Except ø125

### How to Order



Standard model no. **-XC89**

Spatter resistant coil scraper, Lube-retainer, Grease for welding (Piston rod: S45C)

### Specifications

Piston rod	S45C (With hard chrome plated)
Scraper	With coil scraper, With Lube-retainer
Grease	Grease for welding
Other specifications	Same as standard type

### Dimensions (Dimensions other than below are the same as standard type.)



[mm]

Bore size	F	Fd	H	ZZ
32	21	28	50	138
40	23.5	33	61	149
50	23	39.5	67	165
63	23	39.5	67	165
80	29	44.5	82	200
100	29	54	82	200

## 24 Spatter Resistant Coil Scraper, Grease for Welding (Piston rod: S45C) **-XC91**

Symbol

With coil scraper and grease for welding

### Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	Except ø125

### How to Order



Standard model no. **-XC91**

Spatter resistant coil scraper, Grease for welding (Piston rod: S45C)

### Specifications

Piston rod	S45C (With hard chrome plated)
Scraper	With coil scraper
Grease	Grease for welding
Other specifications	Same as standard type

### Dimensions (Dimensions other than below are the same as standard type.)



[mm]

Bore size	H	ZZ
32	47	135
40	58	146
50	67	165
63	67	165
80	81	199
100	81	199

## 25 Cylinder with Heat Resistant Reed Auto Switch (−10 to 120°C)

Symbol  
**-X1184**

### Applicable Series

Description	Model	Action	Note
Standard type	MB	Double acting, Single rod	

### How to Order

**MDB** **Standard model no.** **Z** – **Pivot bracket** **Rod end bracket** – **Heat resistant reed auto switch** – **X1184**

Switch model		Number of switches	
Symbol	Description	Symbol	Description
<b>Nil</b>	Without switch	<b>S</b>	1 pc.
<b>B30</b>	D-B30	<b>Nil</b>	2 pcs.
<b>B30J</b>	D-B30J	<b>n</b>	n pcs.
<b>B31</b>	D-B31		
<b>B31J</b>	D-B31J		
<b>B35</b>	D-B35		
<b>B35J</b>	D-B35J		

Cylinder with heat resistant reed auto switch

\* Refer to the **WEB catalog** or the Best Pneumatics No. 2 for details about the D-B3 auto switch and the Specific Product Precautions.


### Specifications

<b>Ambient temperature range</b>	−10°C to 120°C
<b>Bore size</b>	40, 50, 63, 80, 100
<b>Seal material</b>	Fluororubber
<b>Grease</b>	Heat resistant grease

### Warning Precautions

Be aware that smoking cigarettes etc. after your hands have come into contact with the grease used in this cylinder can create a gas that is hazardous to humans.

### Dimensions (Dimensions other than below are the same as standard type.)



Bore size	S	ZZ	Hs	RA	RB	Minimum mounting stroke		Auto switch mounting bracket part number
						Other than center trunnion	Center trunnion	
<b>40</b>	99	154	57.5	2.5	14.5	1 pc.: 50 st or more 2 pcs.: Different surfaces 50 st or more	200 st or more	BMB2-040
<b>50</b>	109	171	63	3.5	14.5		200 st or more	BMB1-050
<b>63</b>	109	171	69.5	0.5	14.5	2 pcs.: Same surface 220 st or more	200 st or more	BMB1-063
<b>80</b>	129	205	78.5	2.5	22.5		210 st or more	BMB1-080
<b>100</b>	129	205	89	1	22		210 st or more	BMB1-100

[mm]



## Series MB

# Specific Product Precautions

Be sure to read this before handling. Refer to the back cover for Safety Instructions. For Actuator and Auto Switch Precautions, refer to “Handling Precautions for SMC Products” and the Operation Manual on the SMC website, <http://www.smcworld.com>

### Adjustment

## Warning

### 1. Do not open the cushion valve beyond the stopper.

Crimping (ø32) or a retaining ring (ø40 to ø100) is provided to prevent the accidental removal of the cushion valve. Do not open the valve beyond the mechanism. If air is supplied, the cushion valve may shoot out from the cover.

Bore size [mm]	Cushion valve width across flats [mm]	Hexagon wrench
32, 40	2.5	JIS 4648 Hexagonal wrench key 2.5
50, 63	3	JIS 4648 Hexagonal wrench key 3
80, 100, 125	4	JIS 4648 Hexagonal wrench key 4

### 2. Use the air cushion at the end of cylinder stroke.

Select the cylinder with bumper if the cushion valve is to be fully opened. Otherwise, tie-rods or piston assembly may be damaged.

### 3. When replacing mounting brackets, use a hexagon wrench.

Bore size [mm]		Bolt	Width across flats [mm]	Tightening torque [N·m]
32, 40		MB-32-48-C1247	4	5.1
50, 63		MB-50-48-C1249	5	11
80, 100	Foot	MB-80-48AC1251	6	25
	Others	MB-80-48BC1251		
125	Foot	CE00008	8	30.1
	Others	CE00032		

### 4. When replacing mounting brackets, tie-rod nuts on the cylinder body become loosened.

After retightening the tie-rod nuts with the proper tightening torque (Refer to Adjustment 3.), mount a mounting bracket.

### 5. Do not disassemble the trunnion type cylinder because the mounting precision is required.

It is difficult to align the axial center of the trunnion with the axial center of the cylinder. Thus, if this type of cylinder is disassembled and reassembled, the required dimensional accuracy cannot be attained, which may lead to malfunctions.


### With Rod Boot

### Handling

## Caution

### 1. Do not turn the piston rod with the rod boot kept locked.

When turning the piston rod, loosen the band once and do not twist the rod boot.





### 2. Set the breathing hole in the rod boot downward or in the direction that prevents entry of dust or water content.


Standard	Double Acting, Single Rod	MB
Standard	Double Acting, Double Rod	MBW
Non-rotating Rod	Double Acting, Single Rod	MBK
Non-rotating Rod	Double Acting, Double Rod	MBKW
With End Lock		MBB
Low Friction		MB□Q
		Auto Switch
		Made to Order

## Safety Instructions

These safety instructions are intended to prevent hazardous situations and/or equipment damage. These instructions indicate the level of potential hazard with the labels of “**Caution**,” “**Warning**” or “**Danger**.” They are all important notes for safety and must be followed in addition to International Standards (ISO/IEC)\*1), and other safety regulations.

 **Caution:** **Caution** indicates a hazard with a low level of risk which, if not avoided, could result in minor or moderate injury.

 **Warning:** **Warning** indicates a hazard with a medium level of risk which, if not avoided, could result in death or serious injury.

 **Danger :** **Danger** indicates a hazard with a high level of risk which, if not avoided, will result in death or serious injury.

\*1) ISO 4414: Pneumatic fluid power – General rules relating to systems.  
ISO 4413: Hydraulic fluid power – General rules relating to systems.  
IEC 60204-1: Safety of machinery – Electrical equipment of machines.  
(Part 1: General requirements)  
ISO 10218-1: Manipulating industrial robots – Safety.  
etc.

### Warning

#### 1. The compatibility of the product is the responsibility of the person who designs the equipment or decides its specifications.

Since the product specified here is used under various operating conditions, its compatibility with specific equipment must be decided by the person who designs the equipment or decides its specifications based on necessary analysis and test results. The expected performance and safety assurance of the equipment will be the responsibility of the person who has determined its compatibility with the product. This person should also continuously review all specifications of the product referring to its latest catalog information, with a view to giving due consideration to any possibility of equipment failure when configuring the equipment.

#### 2. Only personnel with appropriate training should operate machinery and equipment.

The product specified here may become unsafe if handled incorrectly. The assembly, operation and maintenance of machines or equipment including our products must be performed by an operator who is appropriately trained and experienced.

#### 3. Do not service or attempt to remove product and machinery/equipment until safety is confirmed.

1. The inspection and maintenance of machinery/equipment should only be performed after measures to prevent falling or runaway of the driven objects have been confirmed.
2. When the product is to be removed, confirm that the safety measures as mentioned above are implemented and the power from any appropriate source is cut, and read and understand the specific product precautions of all relevant products carefully.
3. Before machinery/equipment is restarted, take measures to prevent unexpected operation and malfunction.

#### 4. Contact SMC beforehand and take special consideration of safety measures if the product is to be used in any of the following conditions.

1. Conditions and environments outside of the given specifications, or use outdoors or in a place exposed to direct sunlight.
2. Installation on equipment in conjunction with atomic energy, railways, air navigation, space, shipping, vehicles, military, medical treatment, combustion and recreation, or equipment in contact with food and beverages, emergency stop circuits, clutch and brake circuits in press applications, safety equipment or other applications unsuitable for the standard specifications described in the product catalog.
3. An application which could have negative effects on people, property, or animals requiring special safety analysis.
4. Use in an interlock circuit, which requires the provision of double interlock for possible failure by using a mechanical protective function, and periodical checks to confirm proper operation.

### Caution

#### 1. The product is provided for use in manufacturing industries.

The product herein described is basically provided for peaceful use in manufacturing industries.  
If considering using the product in other industries, consult SMC beforehand and exchange specifications or a contract if necessary.  
If anything is unclear, contact your nearest sales branch.

## Limited warranty and Disclaimer/ Compliance Requirements

The product used is subject to the following “Limited warranty and Disclaimer” and “Compliance Requirements”.

Read and accept them before using the product.

### Limited warranty and Disclaimer

1. The warranty period of the product is 1 year in service or 1.5 years after the product is delivered, whichever is first.\*2)  
Also, the product may have specified durability, running distance or replacement parts. Please consult your nearest sales branch.
2. For any failure or damage reported within the warranty period which is clearly our responsibility, a replacement product or necessary parts will be provided.  
This limited warranty applies only to our product independently, and not to any other damage incurred due to the failure of the product.
3. Prior to using SMC products, please read and understand the warranty terms and disclaimers noted in the specified catalog for the particular products.

#### \*2) Vacuum pads are excluded from this 1 year warranty.

A vacuum pad is a consumable part, so it is warranted for a year after it is delivered.  
Also, even within the warranty period, the wear of a product due to the use of the vacuum pad or failure due to the deterioration of rubber material are not covered by the limited warranty.

### Compliance Requirements

1. The use of SMC products with production equipment for the manufacture of weapons of mass destruction (WMD) or any other weapon is strictly prohibited.
2. The exports of SMC products or technology from one country to another are governed by the relevant security laws and regulations of the countries involved in the transaction. Prior to the shipment of a SMC product to another country, assure that all local rules governing that export are known and followed.

### Caution

#### SMC products are not intended for use as instruments for legal metrology.

Measurement instruments that SMC manufactures or sells have not been qualified by type approval tests relevant to the metrology (measurement) laws of each country. Therefore, SMC products cannot be used for business or certification ordained by the metrology (measurement) laws of each country.

### Revision history

**Edition B** \* Standard type, Double rod

- \* Added Made to Order: Heat resistant cylinder (-XB6),  
With heavy duty scraper (-XC4), Adjustable stroke cylinder (-XC8, 9)  
and Dual stroke cylinder (-XC10, 11), etc.
- \* Number of pages increased from 24 to 44.

RW

**Edition C** \* Added ø125 to standard type.

\* Changed standard strokes tables.

- \* Added current models, Non-rotating rod type (MBK, MBKW), With end lock (MBB) and Low friction type (MB□Q).
- \* Number of pages increased from 44 to 64.

SZ

**Edition D** \* Non-rotating rod type: Changed to the MBK-Z series.

- \* Non-rotating rod type: Changed to the MBKW-Z series.

TX

## Safety Instructions

Be sure to read the “Handling Precautions for SMC Products” (M-E03-3) and “Operation Manual” before use.